

Impact Driver LXT

DTD158Z



Product Description

• 18V LXT • BL • XPT • 170 Nm • 0 - 3 600 min⁻¹

Easy-to Handle Basic Impact Driver

This model is an affordable LXT version based on the current model DTD153, maintaining its core performance while enhancing price competitiveness.

DTD158Z comes without battery, charger and carry case.

Product Features

- ⊙ Maximum Fastening Torque of 170 N·m
- ⊙ Easy-to Handle Basic Impact Driver
- ⊙ One-touch Bit Installation
- ⊙ LED Job Light with preglow and afterglow functions

Product Specifications

Capacity	Machine Screw : M4 - M8
	Standard Bolt : M5 - M16
	High Strength Bolt: M5 - M14
	Coarse Thread (in length) : 22 - 125mm
Max Fastening Torque	170 N·m
Impacts per minute	0 - 3,600 min ⁻¹
No load speed	0 - 3,400 min ⁻¹
Dimensions (LxWxH)	125x81x233 mm (with BLB182)
Net Weight	1.3 kg (with BLB182)
Capacity	Machine Screw : M4 - M8
	Standard Bolt : M5 - M16
	High Strength Bolt: M5 - M14
	Coarse Thread (in length) : 22 - 125mm
Max Fastening Torque	170 N·m
Impacts per minute	0 - 3,600 min ⁻¹
No load speed	0 - 3,400 min ⁻¹
Dimensions (LxWxH)	125x81x233 mm (with BLB182)
Net Weight	1.3 kg (with BLB182)

Standard Equipment

- ⊙ Hook

More info

<https://makita.ae/product/impact-driver-lxt-dtd158z/>