

Impact Driver LXT

DTP141RFJ



Product Description

18V LXT • 1/4" • 150 Nm • 0 - 2 700 min⁻¹

Multipurpose 4-mode impact driver with three power settings

A 4-mode impact driver with an electronic torque control and four functions. The functions are impact driver, percussion drill, two-speed drill and screwdriver. Includes 2 x 3,0 Ah batteries and a charger in a Makpac case.

Product Features

- ⊙ LED light illuminates the work site
- ⊙ Body model - delivered without battery and charger.
- ⊙ Battery protection system automatically shuts off power when the battery level is low

Barcode

88381673518

Product Specifications

Torque setting	9
Max. Drilling Diameter in Steel	10 mm
Max. Drilling Diameter in Wood	21 mm
No load speed screwdriver	0 - 300 / 0 - 1100 min ⁻¹
Vibration Level (3 axes), Impact Drilling	13,0 m/s ²
Tool weight with battery (EPTA)	1,5 - 1,9 kg
Brushless Motor	YES
Battery Voltage	18 V
Vibration Level (3 axes), Fastening Bolt	10,5 m/s ²
Sound Pressure Level	85 dB(A)
Capacity machine screw	M4 - M8
Vibration Uncertainty (K Factor)	1,5 m/s ²
Driving Shank	0.25 "
Product Dimensions (L x W x H):	171 x 79 x 250 mm
Tightening Capacity High Tensile Bolt	M5 - M12
Max. fastening torque Hard/Soft	22 / 13 Nm
Sound Power Level (L_{WA})	96 dB(A)
Impacts per Minute (IPM)	0 - 1200 / 2400 / 3200 min ⁻¹
Max Fastening Torque Impact Drill	150 Nm
Impacts per minute, Hammer drill mode	0 - 8400 / 32400 min ⁻¹
Voltage LXT	1

System	LXT 18V/36V
Product net weight (new)	1,2 kg
Tightening Capacity Standard Bolt	M5 - M14
Noise Uncertainty (K Factor)	3 dB(A)
Tool Category	Screwing and Drilling
Max. Drilling Diameter in Masonry	8 mm
Max. Drilling Diameter in Concrete	8 mm
Width	79 mm
No load speed	0 - 1300 / 2200 / 2700 min ⁻¹

Standard Equipment

- ⊙ 1pc DC18RC Fast Charger
- ⊙ 2pcs BL1830B (3.0Ah) 18V LXT Battery
- ⊙ Makpac Case

More info

<https://makita.ae/product/impact-driver-lxt-dtp141rfj/>