

## Impact Driver LXT DTS141RFJ



### Product Description

18V LXT • 1/4" • 40 Nm • 0 - 3 200 min<sup>-1</sup>

**Extremely quiet screwdriver with oil-dampened impact mechanism**

Extremely quiet impact screwdriver. Oil-dampened shock absorber effectively suppresses sound. Extremely short and light thanks to brushless carbon-free engine and compact impact mechanism. Includes 2 x 3,0 Ah batteries and a charger in a Makpac case.

### Product Features

- ⊙ Body model - delivered without battery and charger.
- ⊙ Battery protection system automatically shuts off power when the battery level is low

### Barcode

88381684521

### Product Specifications

|   |                      |
|---|----------------------|
| <b>Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)</b> | Li-ion               |
| <b>Tool weight with battery (EPTA)</b>            | 1,2 - 1,6 kg         |
| <b>Brushless Motor</b>                            | YES                  |
| <b>Battery Voltage</b>                            | 18 V                 |
| <b>Vibration Level (3 axes), Fastening Bolt</b>   | 7,0 m/s <sup>2</sup> |
| <b>Sound Pressure Level</b>                       | 80 dB(A)             |
| <b>Capacity machine screw</b>                     | M4 - M8              |
| <b>Vibration Uncertainty (K Factor)</b>           | 1,5 m/s <sup>2</sup> |
| <b>Driving Shank</b>                              | 0.25 "               |
| <b>Product Dimensions (L x W x H):</b>            | 136 x 79 x 240 mm    |
| <b>Tightening Capacity High Tensile Bolt</b>      | M5 - M6              |
| <b>Sound Power Level (L<sub>WA</sub>)</b>         | 88 dB(A)             |

|  |  |
|--|--|
| <b>Impacts per Minute (IPM)</b>          | 0 - 1400 / 2200 / 2700 min <sup>-1</sup> |
| <b>Max Fastening Torque Impact Drill</b> | 40 Nm                                    |
| <b>Voltage LXT</b>                       | 1  |
| <b>System</b>                            | LXT 18V/36V                              |
| <b>Product net weight (new)</b>          | 0,85 kg                                  |
| <b>Tightening Capacity Standard Bolt</b> | M5 - M8                                  |
| <b>Noise Uncertainty (K Factor)</b>      | 3 dB(A)                                  |
| <b>Tool Category</b>                     | Screwing and Drilling                    |
| <b>No load speed</b>                     | 0 - 1200 / 2000 / 3200 min <sup>-1</sup> |

#### Standard Equipment

- ⊙ 1pc DC18RC Fast Charger
- ⊙ 2pcs BL1830B (3.0Ah) 18V LXT Battery
- ⊙ Makpac Case

#### More info

<https://makita.ae/product/impact-driver-lxt-dts141rfj/>