

Impact Driver LXT DTS141RTJ



Product Description

18V LXT • 1/4" • 40 Nm • 0 - 3 200 min⁻¹

An oil-impulse driver with quiet operation and three power settings

An extremely quiet impact driver. Oil-impulse technology guarantees lower noise levels. A light and compact structure, thanks to a brushless engine and compact drive system. Includes 2 x 5,0 Ah batteries and a charger in a Makpac case.

Product Features

- ⊙ Body model - delivered without battery and charger.
- ⊙ Battery protection system automatically shuts off power when the battery level is low

Barcode

88381816526

Product Specifications

Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
Tool weight with battery (EPTA)	1,2 - 1,6 kg
Brushless Motor	YES
Battery Voltage	18 V
Vibration Level (3 axes), Fastening Bolt	7,0 m/s ²
Sound Pressure Level	80 dB(A)
Capacity machine screw	M4 - M8
Vibration Uncertainty (K Factor)	1,5 m/s ²
Driving Shank	0.25 "
Product Dimensions (L x W x H):	136 x 79 x 240 mm
Tightening Capacity High Tensile Bolt	M5 - M6
Sound Power Level (L_{WA})	88 dB(A)
Impacts per Minute (IPM)	0 - 1400 / 2200 / 2700 min ⁻¹
Max Fastening Torque Impact Drill	40 Nm
Voltage LXT	1
System	LXT 18V/36V
Product net weight (new)	0,85 kg
Tightening Capacity Standard Bolt	M5 - M8

Noise Uncertainty (K Factor)	3 dB(A)
Tool Category	Screwing and Drilling
No load speed	0 - 1200 / 2000 / 3200 min ⁻¹

Standard Equipment

- ⊙ 1pc DC18RC Fast Charger
- ⊙ 2pcs BL1850B (5.0Ah) 18V LXT Battery
- ⊙ Makpac Case

More info

<https://makita.ae/product/impact-driver-lxt-dts141rtj/>