

## Impact Driver LXT

# DTS141RTJ



### Product Description

18V LXT • 1/4" • 40 Nm • 0 - 3 200 min<sup>-1</sup>

**An oil-impulse driver with quiet operation and three power settings**

An extremely quiet impact driver. Oil-impulse technology guarantees lower noise levels. A light and compact structure, thanks to a brushless engine and compact drive system. Includes 2 x 5,0 Ah batteries and a charger in a Makpac case.

### Product Features

- ⊙ Body model - delivered without battery and charger.
- ⊙ Battery protection system automatically shuts off power when the battery level is low

### Barcode

88381816526

### Product Specifications

<b>Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)</b>	Li-ion
<b>Tool weight with battery (EPTA)</b>	1,2 - 1,6 kg
<b>Brushless Motor</b>	YES
<b>Battery Voltage</b>	18 V
<b>Vibration Level (3 axes), Fastening Bolt</b>	7,0 m/s <sup>2</sup>
<b>Sound Pressure Level</b>	80 dB(A)
<b>Capacity machine screw</b>	M4 - M8
<b>Vibration Uncertainty (K Factor)</b>	1,5 m/s <sup>2</sup>
<b>Driving Shank</b>	0.25 "
<b>Product Dimensions (L x W x H):</b>	136 x 79 x 240 mm
<b>Tightening Capacity High Tensile Bolt</b>	M5 - M6
<b>Sound Power Level (L<sub>WA</sub>)</b>	88 dB(A)
<b>Impacts per Minute (IPM)</b>	0 - 1400 / 2200 / 2700 min <sup>-1</sup>
<b>Max Fastening Torque Impact Drill</b>	40 Nm
<b>Voltage LXT</b>	1
<b>System</b>	LXT 18V/36V
<b>Product net weight (new)</b>	0,85 kg
<b>Tightening Capacity Standard Bolt</b>	M5 - M8

<b>Noise Uncertainty (K Factor)</b>	3 dB(A)
<b>Tool Category</b>	Screwing and Drilling
<b>No load speed</b>	0 - 1200 / 2000 / 3200 min <sup>-1</sup>

#### Standard Equipment

- ⊙ 1pc DC18RC Fast Charger
- ⊙ 2pcs BL1850B (5.0Ah) 18V LXT Battery
- ⊙ Makpac Case

#### More info

<https://makita.ae/product/impact-driver-lxt-dts141rtj/>