

## Impact Driver XGT TD001GM201



### Product Description

40V MAX XGT • 1/4" • 220 Nm • 0 - 3 700 min<sup>-1</sup>

#### Extremely compact impact driver with six stroke settings

Powerful brushless Impact Driver with multiple operation modes. The machine has an excellent ability to perform in heavy-duty continuous tightening. The machine has 4-speed power selection and 6 Assist modes. This machine is a genuine solution for high demand industrial users. 2 x 4,0 Ah battery and rapid charger in a case included

### Product Features

- ⊙ LED light illuminates the work site
- ⊙ Low power consumption thanks to brushless motor
- ⊙ XPT (Extreme Protection Technology) is engineered for improved dust and water resistance for operation in harsh job site conditions
- ⊙ The rubber grip on the handle ensures a good working grip
- ⊙ Battery protection system automatically shuts off power when the battery level is low

### Barcode

88381896153

### Product Specifications

|   |                       |
|---|-----------------------|
| <b>Tool weight with battery (EPTA)</b>            | 1,7 - 2,3 kg          |
| <b>Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)</b> | Li-ion                |
| <b>Battery Voltage</b>                            | 40 V                  |
| <b>Brushless Motor</b>                            | YES                   |
| <b>Vibration Level (3 axes), Fastening Bolt</b>   | 10,0 m/s <sup>2</sup> |
| <b>Sound Pressure Level</b>                       | 99 dB(A)              |
| <b>Capacity machine screw</b>                     | M4 - M8               |
| <b>Vibration Uncertainty (K Factor)</b>           | 1,5 m/s <sup>2</sup>  |

|  |   |
|--|---|
| <b>Driving Shank</b>                         | 0.25 "  |
| <b>Tightening Capacity High Tensile Bolt</b> | M5 - M14  |
| <b>Product Dimensions (L x W x H):</b>       | 120 x 86 x 250 mm                               |
| <b>Product net weight (new)</b>              | 1,0 kg  |
| <b>Impacts per Minute (IPM)</b>              | 0 - 1100 / 2600 / 3600 / 4400 min <sup>-1</sup> |
| <b>System</b>                                | XGT 40Vmax/80V max                              |
| <b>Max Fastening Torque Impact Drill</b>     | 20 / 50 / 170 / 220 Nm                          |
| <b>Sound Power Level (L<sub>WA</sub>)</b>    | 107 dB(A)                                       |
| <b>Voltage XGT</b>                           | 1   |
| <b>Tightening Capacity Standard Bolt</b>     | M5 - M16  |
| <b>Noise Uncertainty (K Factor)</b>          | 3 dB(A)   |
| <b>Tool Category</b>                         | Screwing and Drilling                           |
| <b>No load speed</b>                         | 0 - 1100 / 2100 / 3200 / 3700 min <sup>-1</sup> |

#### Standard Equipment

- ⊙ 1pc DC40RA Fast Charger
- ⊙ 2pcs x BL4040 (4.0Ah) 40V MAX XGT Battery
- ⊙ Makpack Case

#### More info

<https://makita.ae/product/impact-driver-xgt-td001gm201/>