

# Impact Driver XGT TD002GZ01



## Product Description

40V MAX XGT • 1/4" • 220 Nm • 0 - 3 700 min<sup>-1</sup>

### Extremely compact impact driver.

Powerful brushless Impact Driver. The maximum torque is 220 Nm and the machine has multiple operation modes for a wide range of applications; 4-speed power selection and 6 Assist modes.

## Product Features

- ⊙ Ergonomically designed handle with soft grip provides increased comfort on the job
- ⊙ Electric brake for maximum productivity and increased operator safety
- ⊙ eXtreme Protection Technology (XPT) is engineered for improved dust and water resistance for operation in harsh conditions
- ⊙ Battery protection circuit protects against overloading, over-discharging and over-heating

## Barcode

88381767804

## Product Specifications

<b>Tool weight with battery (EPTA)</b>	1,7 - 2,9 kg
<b>Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)</b>	Li-ion
<b>Battery Voltage</b>	40 V
<b>Brushless Motor</b>	YES
<b>Vibration Level (3 axes), Fastening Bolt</b>	12,9 m/s <sup>2</sup>
<b>Sound Pressure Level</b>	94 dB(A)
<b>Capacity machine screw</b>	M4 - M8
<b>Vibration Uncertainty (K Factor)</b>	1,5 m/s <sup>2</sup>
<b>Driving Shank</b>	0.25 "
<b>Tightening Capacity High Tensile Bolt</b>	M5 - M14

<b>Product Dimensions (L x W x H):</b>	119 x 86 x 252 mm
<b>Product net weight (new)</b>	1,0 kg
<b>Impacts per Minute (IPM)</b>	0 - 1400 / 2600 / 3600 / 4600 min <sup>-1</sup>
<b>System</b>	XGT 40Vmax/80V max
<b>Max Fastening Torque Impact Drill</b>	20 / 50 / 170 / 220 Nm
<b>Sound Power Level (L<sub>WA</sub>)</b>	105 dB(A)
<b>Voltage XGT</b>	1
<b>Tightening Capacity Standard Bolt</b>	M5 - M16
<b>Noise Uncertainty (K Factor)</b>	3 dB(A)
<b>Tool Category</b>	Screwing and Drilling
<b>No load speed</b>	0 - 1100 / 2100 / 3200 / 3700 min <sup>-1</sup>

#### Standard Equipment

- ⊙ Sold without Battery or Charger

#### More info

<https://makita.ae/product/impact-driver-xgt-td002gz01/>