Impact Driver XGT TD003GZ

makita



Product Description

40V MAX XGT • 1/4" • 210 Nm • 0 - 3 700 min⁻¹ Cordless impact driver powered by 40Vmax XGT Li-Ion battery.

Powerful brushless Impact Driver with multiple operation modes. The machine has an excellent ability to perform in heavy-duty continuous tightening. The machine has 4-speed power selection and T-mode assist function for thin metals. This machine is a genuine solution for high demand industrial users. (Sold without battery and Charger)

Product Features

LED light illuminates the work site

• Low power consumption thanks to brushless motor

 \odot XPT (Extreme Protection Technology) is engineered for improved dust and water resistance for operation in harsh job site conditions

• The rubber grip on the handle ensures a good working grip

Battery protection system automatically shuts off power when the battery level is low
 In the system automatically shuts off power when the battery level is low
 In the system automatically shuts off power when the battery level is low
 In the system automatically shuts off power when the battery level is low
 In the system automatically shuts off power when the battery level is low
 In the system automatically shuts off power when the battery level is low
 In the system automatically shuts off power when the battery level is low
 In the system automatically shuts off power when the battery level is low
 In the system automatically shuts off power when the system automatically
 In the system automatically shuts off power when the system automatically
 In the system automatically

Barcode

88381777728

Product Specifications

Tool weight with battery (EPTA)	1,7 - 2,9 kg
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
Battery Voltage	40 V
Brushless Motor	YES
Vibration Level (3 axes), Fastening Bolt	11,9 m/s ²
Sound Pressure Level	95 dB(A)
Capacity machine screw	M4 - M8
Vibration Uncertainty (K Factor)	1,5 m/s ²
Driving Shank	0.25 "
Tightening Capacity High Tensile Bolt	M5 - M14
Product Dimensions (L x W x H):	121 x 86 x 252 mm

Product net weight (new)	1,0 kg
Impacts per Minute (IPM)	0 - 1400 / 2600 / 3600 / 4100 min ⁻¹
System	XGT 40Vmax/80V max
Max Fastening Torque Impact Drill	20 / 50 / 170 / 210 Nm
Sound Power Level (L _{wa})	106 dB(A)
Voltage XGT	1
Tightening Capacity Standard Bolt	M5 - M16
Noise Uncertainty (K Factor)	3 dB(A)
Tool Category	Screwing and Drilling
No load speed	0 - 1100 / 2100 / 3200 / 3700 min ⁻¹

Standard Equipment

 \circledast Sold without Battery or Charger

More info

https://makita.ae/product/impact-driver-xgt-td003gz/