

## Impact Wrench

# 6906



### Product Description

115V-220V: 850 W • 230-240V: 620 W • 3/4" • 588 Nm

#### For high-torque applications

A powerful 3/4" drive impact wrench with an 850 W motor and max. torque of 588 Nm. Ideal for applications that require a high fastening torque. A rocker switch for easy reversing and a side handle for added comfort.

### Product Specifications

Drive Square	3/4" "
Power Supply Cord	2,5 m
Product Dimensions (L x W x H):	327 x 95 x 237 mm
Tightening Capacity High Tensile Bolt	M16 - M20
Noise Uncertainty (K Factor)	3 dB(A)
Tightening Capacity Standard Bolt	M16 - M22
Weight Without Cable (EPTA)	5,6 kg
Vibration Uncertainty (K Factor)	2,0 m/s <sup>2</sup>
Continuous Input Power (115V / 220V)	850 W
Continuous Input Power (230 / 240V)	620 W
Sound Pressure Level	101 dB(A)
Vibration Level (3 axes), Fastening Bolt	16,5 m/s <sup>2</sup>
Tool Category	Screwing and Drilling
No load speed	0 - 1700 min <sup>-1</sup>
Impacts per Minute (IPM)	1600 min <sup>-1</sup>
Max Fastening Torque Impact Drill	588 Nm
Sound Power Level (L <sub>WA</sub> )	109 dB(A)
Vibration Level (3 axes)	16,5 m/s <sup>2</sup>
Product net weight (new)	5,6 kg

### More info

<https://makita.ae/product/impact-wrench-6906/>