

## Impact Wrench CXT TW161DSME



### Product Description

12V MAX • 1/2" • 165 Nm • 0 - 2 400 min<sup>-1</sup>

#### **Very compact impact wrench for working in tight spaces**

Compact and lightweight impact wrench for 1/2" sockets. Torque of 165 Nm. Ideal for working in tight spaces. LED light which illuminates the job site makes working more easy and convenient. Package includes two 4,0 Ah batteries and a charger in a case.

### Product Features

- ◉ LED light illuminates the work site
- ◉ Battery protection system automatically shuts off power when the battery level is low
- ◉ Reverse Rotation Auto-Stop Mode stops in 0.2 seconds after the bolt/nut loosened enough
- ◉ BL motor eliminates carbon brushes, enabling the BL motor to run cooler and more efficiently for longer life
- ◉ Ergonomic shape fits like a glove with even pressure and easy control
- ◉ Ideal for working in tight spaces and overhead applications
- ◉ Electric brake for increased operator safety

### Barcode

88381880961

### Product Specifications

|                                 |              |
|---------------------------------|--------------|
| Tool weight with battery (EPTA) | 1,1 - 1,2 kg |
| Drive Square                    | 0.5 "        |
| Battery Voltage                 | 12 V         |
| Brushless Motor                 | YES          |

|  |                                       |
|--|---------------------------------------|
| <b>Sound Pressure Level</b>                  | 93 dB(A)                              |
| <b>CXT Battery</b>                           | 1                                     |
| <b>Vibration Uncertainty (K Factor)</b>      | 1,5 m/s <sup>2</sup>                  |
| <b>Tightening Capacity High Tensile Bolt</b> | M5 - M10                              |
| <b>Product Dimensions (L x W x H):</b>       | 150 x 66 x 213 mm                     |
| <b>Product net weight (new)</b>              | 0,83 kg                               |
| <b>Impacts per Minute (IPM)</b>              | 0 - 3600 / 0 - 2000 min <sup>-1</sup> |
| <b>System</b>                                | CXT 12Vmax                            |
| <b>Max Fastening Torque Impact Drill</b>     | 165 Nm                                |
| <b>Sound Power Level (L<sub>WA</sub>)</b>    | 104 dB(A)                             |
| <b>Vibration Level (3 axes)</b>              | 8,0 m/s <sup>2</sup>                  |
| <b>Max Output Power</b>                      | 170 W                                 |
| <b>Tightening Capacity Standard Bolt</b>     | M8 - M16                              |
| <b>Noise Uncertainty (K Factor)</b>          | 3 dB(A)                               |
| <b>Tool Category</b>                         | Screwing and Drilling                 |
| <b>No load speed</b>                         | 0 - 2400 / 0 - 1300 min <sup>-1</sup> |

#### Standard Equipment

- ⊙ 1pc DC10SB Fast Charger
- ⊙ 2pcs BL1041B (4.0Ah) CXT Battery
- ⊙ Carry Case

#### More info

<https://makita.ae/product/impact-wrench-cxt-tw161dsme/>