

## Impact Wrench

# TW0350



### Product Description

400 W • 1/2" • 350 Nm

#### High-torque impact wrench

An efficient 1/2" drive impact wrench with a 400 W motor and max. torque of 350 Nm. An easy-to-use tool for high-torque applications. Reverse function.

### Product Features

- ⦿ The rubber coating on the handle ensures a firm working grip

### Barcode

88381051309

### Product Specifications

Drive Square	0.5 "
Vibration Level (3 axes), Fastening Bolt	11,5 m/s <sup>2</sup>
Sound Pressure Level	93 dB(A)
Power Supply Cord	2,5 m
Continuous Input Power	400 W
Vibration Uncertainty (K Factor)	1,5 m/s <sup>2</sup>
Tightening Capacity High Tensile Bolt	M12 - M16
Product Dimensions (L x W x H):	283 x 87 x 233 mm
Product net weight (new)	3,0 kg
Impacts per Minute (IPM)	0 - 2000 min <sup>-1</sup>
Sound Power Level (L <sub>WA</sub> )	104 dB(A)
Max Fastening Torque Impact Drill	350 Nm
Vibration Level (3 axes)	11,5 m/s <sup>2</sup>
Max Output Power	350 W
Weight Without Cable (EPTA)	3,0 kg
Tightening Capacity Standard Bolt	M12 - M22
Noise Uncertainty (K Factor)	3 dB(A)
Tool Category	Screwing and Drilling
No load speed	0 - 2000 min <sup>-1</sup>

### More info

<https://makita.ae/product/impact-wrench-tw0350/>