



## Impact Wrench XGT TW001GM201



### Product Description

40V MAX XGT • 3/4" • 1 800 Nm • 0 - 2500 min<sup>-1</sup>

#### High torque, brushless impact wrench with three power settings for heavy-duty work

A powerful, brushless 3/4" drive impact wrench with a fastening torque of up to 1 800 Nm. Three different power settings. Equipped with an LED light for added lighting, this tool is ideal for applications that require high fastening torque. Includes 2 x 4,0 Ah batteries and a charger in a Makpac case.

### Product Features

- ◎ Brushless maintenance-free and long-life motor
- ◎ XPT (Extreme Protection Technology) is engineered for improved dust and water resistance for operation in harsh job site conditions
- ◎ Electronic 4 stage impact power selection for added versatility
- ◎ Reverse Rotation Auto Stop Mode stops after the bolt/nut loosened enough
- ◎ Twin LED job light x 2 with preglow and afterglow functions
- ◎ Ergonomically designed handle with rubberized soft grip
- ◎ 3 modes of reaction time for automatic stop available both in forward and reverse rotation modes
- ◎ Battery protection system automatically shuts off power when the battery level is low

### Barcode

88381721059

### Product Specifications

<b>Drive Square</b>	0.75 "
<b>Tool weight with battery (EPTA)</b>	3,9 - 5,1 kg
<b>Battery Voltage</b>	40 V
<b>Brushless Motor</b>	YES
<b>Vibration Level (3 axes), Fastening Bolt</b>	18,5 m/s <sup>2</sup>
<b>Sound Pressure Level</b>	103 dB(A)
<b>Vibration Uncertainty (K Factor)</b>	2,0 m/s <sup>2</sup>
<b>Tightening Capacity High Tensile Bolt</b>	M10 - M27
<b>Product Dimensions (L x W x H):</b>	217 x 94 x 303 mm
<b>Product net weight (new)</b>	3,2 kg

<b>Impacts per Minute (IPM)</b>	0 - 1900 / 2200 / 2400 / 2500 min <sup>-1</sup>
<b>System</b>	XGT 40Vmax/80V max
<b>Sound Power Level (L<sub>WA</sub>)</b>	111 dB(A)
<b>Max Fastening Torque Impact Drill</b>	450 / 840 / 1500 / 1800 Nm
<b>Max Output Power</b>	700 W
<b>Voltage XGT</b>	1
<b>Tightening Capacity Standard Bolt</b>	M12 - M36
<b>Noise Uncertainty (K Factor)</b>	3 dB(A)
<b>Tool Category</b>	Screwing and Drilling
<b>Nut-busting torque</b>	2050 Nm
<b>No load speed</b>	0 - 950 / 1150 / 1400 / 1800 min <sup>-1</sup>

### Standard Equipment

- ◎ 1pc DC40RA Fast Charger
- ◎ 2pcs x BL4040 (4.0Ah) 40V MAX XGT Battery
- ◎ Makpack Case

### More info

<https://makita.ae/product/impact-wrench-xgt-tw001gm201/>