

Impact Wrench XGT TW005GZ

Product Description

40V MAX XGT • 1/2" • 350 Nm • 0 - 4000 min⁻¹

High torque, brushless impact wrench with three power settings for heavy-duty work

Powerful and extra-compact, 144 mm-long, 1/2" drive impact wrench. Small size and light weight make this tool easy to use, while offering a max. fastening torque of 350 Nm. Four power settings. A handy LED light. Tool only, battery and charger not included.



Product Features

- ⊙ Brushless maintenance-free and long-life motor
- ⊙ Electronic 4 stage impact power selection for added versatility
- ⊙ 3 modes of reaction time for automatic stop available both in forward and reverse rotation modes
- ⊙ Reverse Rotation Auto Stop Mode stops after the bolt/nut loosened enough
- ⊙ Twin LED lights with preglow and afterglow functions
- ⊙ XPT (Extreme Protection Technology) is engineered for improved dust and water resistance for operation in harsh job site conditions
- ⊙ Ergonomically designed handle with rubberized soft grip
- ⊙ Style of socket retention: Pin detent
- ⊙ Battery protection system automatically shuts off power when the battery level is low

Barcode

88381727020

Product Specifications

| | |
|---------------------------------|--------------|
| Drive Square | 0.5 " |
| Tool weight with battery (EPTA) | 1,9 - 3,1 kg |
| Battery Voltage | 40 V |

| | |
|---|---|
| Brushless Motor | YES |
| Vibration Level (3 axes), Fastening Bolt | 16,5 m/s ² |
| Sound Pressure Level | 99 dB(A) |
| Vibration Uncertainty (K Factor) | 1,5 m/s ² |
| Tightening Capacity High Tensile Bolt | M10 - M16 |
| Product Dimensions (L x W x H): | 144 x 86 x 253 mm |
| Product net weight (new) | 1,3 kg |
| Impacts per Minute (IPM) | 0 - 1800 / 2600 / 3400 / 4000 min ⁻¹ |
| System | XGT 40Vmax/80V max |
| Max Fastening Torque Impact Drill | 100 / 160 / 210 / 350 Nm |
| Sound Power Level (L_{WA}) | 110 dB(A) |
| Voltage XGT | 1 |
| Tightening Capacity Standard Bolt | M10 - M20 |
| Noise Uncertainty (K Factor) | 3 dB(A) |
| Tool Category | Screwing and Drilling |
| Nut-busting torque | 630 Nm |
| No load speed | 0 - 1000 / 1800 / 2600 / 3200 min ⁻¹ |

Standard Equipment

⊙ Sold without Battery or Charger

More info

<https://makita.ae/product/impact-wrench-xgt-tw005gz/>