

# Lawn Mower LXT

## DLM532Z

### Product Description

36V (18Vx2) LXT • 53 cm • 70 L

**Strong steel frame driven cordless lawnmower with self propelled function.**

Strong steel frame Driving and bio-cutting, collecting, side discharge cordless lawnmower. Centralized cutting height adjustment and ball-bearing wheels, cutting width 53 cm. Infinitely variable speed control, load sensing and four battery bay, recommended cutting area of 2,300 m<sup>2</sup>. Tool only, battery and charger not included.



### Product Features

- ⊙ Shower-proof construction, IPX4
- ⊙ Battery protection circuit protects against overloading, over-discharging and over-heating

### Barcode

88381894579

### Product Specifications

Cutting height positions	10
RPM (Soft no load mode)	2300 / 2800 min <sup>-1</sup>
Continuous use 18V / 6.0 Ah battery	40 min
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
Rear Wheel Diameter	23 cm
Tool weight with battery (EPTA)	39,0 - 43,5 kg
Brushless Motor	YES
Battery Voltage	2 x 18 V
Propelling Speed	2,5 - 5,0 km/h
Collecting Box Capacity	70 L
Sound Pressure Level	80,9 dB(A)
Product Dimensions (L x W x H):	1630 - 1715 x 590 x 990 - 1095 mm
Actual mowing area 6,0 Ah x 4	1700 - 2300 m <sup>2</sup>
Vibration Level (3 axes)	≤ 2,5 m/s <sup>2</sup>
Cumulative	1
Front Wheel Diameter	23 cm
Sound Power Level (L <sub>WA</sub> )	91,9 dB(A)
Voltage LXT	1
System	LXT 18V/36V
Product net weight (new)	37,1 kg
Width of Mowing Deck	53,4 cm
Mowing Height	20-100 mm

Vibration Uncertainty (K Factor)	1,5 m/s <sup>2</sup>
Noise Uncertainty (K Factor)	3 dB(A)
Self-Propelled	1
Bio cutting	1
RPM (noise reduction mode)	2300 min <sup>-1</sup>
Tool Category	Lawn Care
No load speed	2300 - 2800 min <sup>-1</sup>

Standard Equipment

⦿ Sold without Battery or Charger

More info

<https://makita.ae/product/lawn-mower-lxt-dlm532z/>