

## Metal Shear LXT DJS101RTJ



### Product Description

18V LXT • 4 300 min<sup>-1</sup>

#### Metal shear with cutting radius of 30 mm

A cordless metal shear for straight and curved cuts with a radius of 30 mm, cuts a clean-edged strip from the middle. Cutting capacity of 2,5 mm for aluminium and 1,0 mm for steel. The tool has a stroke rate of 4 300 min<sup>-1</sup> and it is equipped with a battery protection system. Includes 2 x 5,0 Ah batteries and a charger in a Makpac case.

### Product Specifications

Cutting Capacity Aluminum (up to 200N/mm <sup>2</sup> )	2,5 mm
Cutting Capacity Stainless Steel (up to 600N/mm <sup>2</sup> )	0,7 mm
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
Vibration Level (3 axes), Cutting Sheet Metal	13,0 m/s <sup>2</sup>
Cutting Capacity Mild Steel (up to 400N/mm <sup>2</sup> )	1,0 mm
Tool weight with battery (EPTA)	1,8 - 2,2 kg
Battery Voltage	18 V
Sound Pressure Level	71 dB(A)
Min. Internal Cutting Radius	30 mm
Product Dimensions (L x W x H):	364 x 78 x 118 mm
Strokes per Minute (SPM)	4300 min <sup>-1</sup>
Voltage LXT	1
System	LXT 18V/36V
Product net weight (new)	1,4 kg
Vibration Uncertainty (K Factor)	1,5 m/s <sup>2</sup>
Noise Uncertainty (K Factor)	3 dB(A)
Min. External Cutting Radius	36 mm
Tool Category	Cutting

### Standard Equipment

- ⊙ 1pc DC18RC Fast Charger
- ⊙ 2pcs BL1850B (5.0Ah) 18V LXT Battery
- ⊙ Makpac Case

### More info

<https://makita.ae/product/metal-shear-lxt-djs101rtj/>