

Metal Shear LXT DJS101Z



Product Description

18V LXT • 4 300 min⁻¹

Metal shear with cutting radius of 30 mm

A cordless metal shear for straight and curved cuts with a radius of 30 mm, cuts a clean-edged strip from the middle. Cutting capacity of 2,5 mm for aluminium and 1,0 mm for steel. The tool has a stroke rate of 4 300 min-1 and it is equipped with a battery protection system. Tool only, battery and charger not included.

Product Specifications

| Cutting Capacity Aluminum (up to 200N/mm²) | 2,5 mm |
|--|------------------------|
| Cutting Capacity Stainless Steel (up to 600N/mm ²) | 0,7 mm |
| Battery Chemistry (Ni-Cd / Ni-MH / Li-ion) | Li-ion |
| Vibration Level (3 axes), Cutting Sheet Metal | 13,0 m/s² |
| Cutting Capacity Mild Steel (up to 400N/mm ²) | 1,0 mm |
| Tool weight with battery (EPTA) | 1,8 - 2,2 kg |
| Battery Voltage | 18 V |
| Sound Pressure Level | 71 dB(A) |
| Min. Internal Cutting Radius | 30 mm |
| Product Dimensions (L x W x H): | 364 x 78 x 118 mm |
| Strokes per Minute (SPM) | 4300 min ⁻¹ |
| Voltage LXT | 1 |
| System | LXT 18V/36V |
| Product net weight (new) | 1,4 kg |
| Vibration Uncertainty (K Factor) | 1,5 m/s² |
| Noise Uncertainty (K Factor) | 3 dB(A) |
| Min. External Cutting Radius | 36 mm |
| Tool Category | Cutting |

Standard Equipment

• Sold without Battery or Charger

More info

https://makita.ae/product/metal-shear-lxt-djs101z/