



Multitool CXT TM30DZ



Product Description

12V MAX • 6 000 – 20 000 min⁻¹

Multitool for cutting, polishing, grout removal and other applications

A handy multi-function tool for a variety of cutting and polishing applications in construction and renovation projects. Powered by a 12V max CXT battery and the oscillating rate can be adjusted between 6 000 and 20 000 min⁻¹. Tool only, battery and charger not included.

Product Features

- ◎ The rubber coating on the handle ensures a firm working grip
- ◎ Soft start and restart protection
- ◎ Battery protection system automatically shuts off power when the battery level is low

Barcode

88381819442

Product Specifications

Tool weight with battery (EPTA)	1,1 - 1,3 kg
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
Vibration Level (3 axes), Sanding	2,5 m/s ²
Battery Voltage	12 V
Sound Pressure Level	81 dB(A)
CXT Battery	1
Pad size (triangle)	93 x 93 x 93 mm
Vibration Level (3 axes), Cutting Chipboard	5,5 m/s ²
Vibration Uncertainty (K Factor)	1,5 m/s ²
Oscillation Angle	2 x 1,6 °
Product Dimensions (L x W x H):	277 x 65 x 98 mm
Product net weight (new)	0,9 kg
System	CXT 12Vmax
Sound Power Level (L_{WA})	92 dB(A)
Vibration Level (3 axes)	1,5 - 10,5 m/s ²
Orbits per Minute	6000-20000 min ⁻¹
Noise Uncertainty (K Factor)	3 dB(A)
Tool Category	Multifunction

Standard Equipment

- ◎ Sold without Battery or Charger

More info

<https://makita.ae/product/multitool-cxt-tm30dz/>