

Nibbler LXT

DJN161RFE



Product Description

18V LXT • 1 900 min⁻¹

Clean and precise cutting of metal and other sheets

A slimline nibbler with a 18V LXT battery that achieves precise arced and straight cuts cleanly. Ideal for cutting profile sheets, such as roofing materials. The nibbler die rotates 360 degrees. A cutting capacity of 2,5 mm for aluminium and 1,6 mm for steel. Includes 2 x 3,0 Ah batteries and a charger in a case.

Product Features

- ⦿ Battery protection circuit protects against overloading, over-discharging and over-heating

Barcode

88381672139

Product Specifications

Cutting Capacity Aluminum (up to 200N/mm ²)	2,5 mm
Cutting Capacity Stainless Steel (up to 600N/mm ²)	1,2 mm
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
Vibration Level (3 axes), Cutting Sheet Metal	6,5 m/s ²
Cutting Capacity Mild Steel (up to 400N/mm ²)	1,6 mm
Tool weight with battery (EPTA)	1,9 - 2,3 kg
Battery Voltage	18 V
Sound Pressure Level	93 dB(A)
Min. Internal Cutting Radius	45 mm
Product Dimensions (L x W x H):	313 x 78 x 189 mm
Strokes per Minute (SPM)	1900 min ⁻¹
Voltage LXT	1
System	LXT 18V/36V
Product net weight (new)	1,6 kg
Vibration Uncertainty (K Factor)	1,5 m/s ²
Noise Uncertainty (K Factor)	3 dB(A)
Min. External Cutting Radius	50 mm
Tool Category	Cutting

Standard Equipment

- ⦿ 1pc DC18RC Fast Charger
- ⦿ 2pcs BL1830B (3.0Ah) 18V LXT Battery

⦿ Carry Case

More info

<https://makita.ae/product/nibbler-lxt-djn161rfe/>