

Percussion Driver Drill CXT

HP333DWAE



Product Description

12V MAX • 30 Nm • 0 - 1 700 min⁻¹

A compact drill for professional screwdriving and drilling

A lightweight drill for screwdriving and drilling with or without hammer action, two power settings. Maximum torque of 30 / 14 Nm. A versatile tool for fitters, builders and maintenance staff. Integrated LED light. Two 2,0 Ah batteries and a charger in a case.

Product Features

- ⦿ Battery protection system automatically shuts off power when the battery level is low

Barcode

88381872973

Product Specifications

| | |
|--|------------------------------------|
| Torque setting | 20 |
| Tool weight with battery (EPTA) | 1,1 - 1,3 kg |
| Max. Drilling Diameter in Steel | 10 mm |
| Max. Drilling Diameter in Wood | 21 mm |
| Battery Chemistry (Ni-Cd / Ni-MH / Li-ion) | Li-ion |
| Vibration Level (3 axes), Impact Drilling | 13,0 m/s ² |
| Battery Voltage | 12 V |
| Sound Pressure Level | 82 dB(A) |
| CXT Battery | 1 |
| Vibration Uncertainty (K Factor) | 1,5 m/s ² |
| Product Dimensions (L x W x H): | 193 x 66 x 212 mm |
| Max. fastening torque Hard/Soft | 30 / 14 Nm |
| Impacts per Minute (IPM) | 0 - 6750 / 25500 min ⁻¹ |
| System | CXT 12Vmax |
| Vibration Level (3 axes) | ≤ 2,5 m/s ² |
| Sound Power Level (L _{WA}) | 93 dB(A) |
| Product net weight (new) | 0,92 kg |
| Noise Uncertainty (K Factor) | 3 dB(A) |
| Max. Drilling Diameter in Concrete | 8 mm |

| | |
|-----------------------------------|----------------------------------|
| Max. Drilling Diameter in Masonry | 8 mm |
| Drill Chuck Capacity | 0,8-10 mm |
| Tool Category | Screwing and Drilling |
| Electronic brake | 1 |
| No load speed | 0 - 450 / 1700 min ⁻¹ |

Standard Equipment

- ⦿ 1pc DC10WC standard charger
- ⦿ 2pcs BL1021B (2.0Ah) CXT Battery
- ⦿ Carry Case

More info

<https://makita.ae/product/percussion-driver-drill-cxt-hp333dwae/>