Percussion Driver Drill LXT

DHP484RTJ

Product Description

18V LXT • 54 Nm • 0 – 2 000 min⁻¹

A powerful, brushless general-use impact drill for screwdriving and drilling

An efficient, brushless drill for professional screwdriving and drilling with or without hammer action, two power settings. Max. torque of 54 / 30 Nm. A versatile tool for fitters, builders and maintenance staff. Integrated LED light. Includes 2 x 5,0 Ah batteries and a charger in a Makpac case.

Product Features

◉ LED light illuminates the work site

◉ Battery protection system automatically shuts off power when the battery level is low

◉ Mechanical 2-speed gearing; High speed mode for speedy drilling in light duty applications; Low speed mode for heavy duty applications requiring high torque

◉ Electric brake for maximum productivity and increased operator safety

◉ Reversing switch is conveniently located

Barcode

88381826228

Product Specifications

Vibration Level (3 axes), Drilling	≤ 2,5 m/s²
Torque setting	21
Max. Drilling Diameter in Steel	13 mm
Max. Drilling Diameter in Wood	38 mm
Vibration Level (3 axes), Impact Drilling	8,0 m/s²
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
Tool weight with battery (EPTA)	1,6 - 1,9 kg
Brushless Motor	YES
Battery Voltage	18 V
Sound Pressure Level	88 dB(A)
Product Dimensions (L x W x H):	182 x 79 x 261 mm
Max. fastening torque Hard/Soft	54 / 30 Nm
Impacts per Minute (IPM)	0 - 7500 / 30000 min⁻¹
Sound Power Level (L$_{WA}$)	99 dB(A)

Voltage LXT	1
System	LXT 18V/36V
Product net weight (new)	1,2 kg
Vibration Uncertainty (K Factor)	1,5 m/s²
Driving Shank	1/2"-20UNF "
Noise Uncertainty (K Factor)	3 dB(A)
Tool Category	Screwing and Drilling
Drill Chuck Capacity	1,5-13 mm
Electronic brake	1
Max. Drilling Diameter in Masonry	13 mm
Max. Drilling Diameter in Concrete	13 mm
No load speed	0 - 500 / 2000 min⁻¹

Standard Equipment

◉ 1pc DC18RC Fast Charger

◉ 2pcs BL1850B (5.0Ah) 18V LXT Battery

◉ Makpac Case

More info

https://makita.ae/product/percussion-driver-drill-lxt-dhp484rtj/