

## Percussion Driver Drill XGT HP001GM201



### Product Description

40V MAX XGT • 140 Nm • 0 - 2 600 min<sup>-1</sup>

#### Rugged, brushless combi drill for heavy-duty screwdriving and drilling

A powerful, brushless drill for professional screwdriving and drilling with or without hammer action, two power settings. A high maximum torque of 140 / 68 Nm. An ideal choice for jobs that require high power and torque. Integrated LED light. Two 4.0 Ah batteries and a rapid charger in a Makpac case.

### Product Features

- ⊙ Jog selector for easy adjustment of mounting torque, visual confirmation of the selected torque on the digital display
- ⊙ XPT (Extreme Protection Technology) is engineered for improved dust and water resistance for operation in harsh job site conditions
- ⊙ Battery protection system automatically shuts off power when the battery level is low
- ⊙ Active Feedback sensing Technology (AFT) stops the engine if the rotation suddenly stops

### Barcode

88381894104

### Product Specifications

<b>Drilling Capacity Wood (Auger Bit)</b>	50 mm
<b>Vibration Level (3 axes), Drilling</b>	≤ 2,5 m/s <sup>2</sup>
<b>Torque setting</b>	41 / 21
<b>Drilling Capacity Wood (Self-feed bit)</b>	76 mm
<b>Tool weight with battery (EPTA)</b>	2,7 - 3,9 kg
<b>Max. Drilling Diameter in Steel</b>	20 mm
<b>Max. Drilling Diameter in Wood</b>	76 mm
<b>Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)</b>	Li-ion
<b>Vibration Level (3 axes), Impact Drilling</b>	6,0 m/s <sup>2</sup>
<b>Battery Voltage</b>	40 V

<b>Brushless Motor</b>	YES
<b>Sound Pressure Level</b>	85 dB(A)
<b>Vibration Uncertainty (K Factor)</b>	1,5 m/s <sup>2</sup>
<b>Driving Shank</b>	1/2"-20UNF "
<b>Product Dimensions (L x W x H):</b>	182 x 86 x 282 mm
<b>Max. fastening torque Hard/Soft</b>	140 / 68 Nm
<b>Impacts per Minute (IPM)</b>	0 - 9750 / 39000 min <sup>-1</sup>
<b>System</b>	XGT 40Vmax/80V max
<b>Sound Power Level (L<sub>WA</sub>)</b>	96 dB(A)
<b>Product net weight (new)</b>	1,7 kg
<b>Voltage XGT</b>	1
<b>Noise Uncertainty (K Factor)</b>	3 dB(A)
<b>Max. Drilling Diameter in Concrete</b>	20 mm
<b>Max. Drilling Diameter in Masonry</b>	20 mm
<b>Drill Chuck Capacity</b>	1,5-13 mm
<b>Tool Category</b>	Screwing and Drilling
<b>Electronic brake</b>	1
<b>No load speed</b>	0 - 650 / 2600 min <sup>-1</sup>

#### Standard Equipment

- ⊙ 1pc DC40RA Fast Charger
- ⊙ 2pcs x BL4040 (4.0Ah) 40V MAX XGT Battery
- ⊙ Makpack Case

#### More info

<https://makita.ae/product/percussion-driver-drill-xgt-hp001gm201/>