



## Percussion Driver Drill XGT HP001GM201



### Product Description

40V MAX XGT • 140 Nm • 0 - 2 600 min<sup>-1</sup>

#### Rugged, brushless combi drill for heavy-duty screwdriving and drilling

A powerful, brushless drill for professional screwdriving and drilling with or without hammer action, two power settings. A high maximum torque of 140 / 68 Nm. An ideal choice for jobs that require high power and torque. Integrated LED light. Two 4.0 Ah batteries and a rapid charger in a Makpac case.

### Product Features

- ◎ Jog selector for easy adjustment of mounting torque, visual confirmation of the selected torque on the digital display
- ◎ XPT (Extreme Protection Technology) is engineered for improved dust and water resistance for operation in harsh job site conditions
- ◎ Battery protection system automatically shuts off power when the battery level is low
- ◎ Active Feedback sensing Technology (AFT) stops the engine if the rotation suddenly stops

### Barcode

88381894104

### Product Specifications

|   |                        |
|---|------------------------|
| <b>Drilling Capacity Wood (Auger Bit)</b>         | 50 mm                  |
| <b>Vibration Level (3 axes), Drilling</b>         | ≤ 2,5 m/s <sup>2</sup> |
| <b>Torque setting</b>                             | 41 / 21                |
| <b>Drilling Capacity Wood (Self-feed bit)</b>     | 76 mm                  |
| <b>Tool weight with battery (EPTA)</b>            | 2,7 - 3,9 kg           |
| <b>Max. Drilling Diameter in Steel</b>            | 20 mm                  |
| <b>Max. Drilling Diameter in Wood</b>             | 76 mm                  |
| <b>Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)</b> | Li-ion                 |
| <b>Vibration Level (3 axes), Impact Drilling</b>  | 6,0 m/s <sup>2</sup>   |
| <b>Battery Voltage</b>                            | 40 V                   |

|   |                                    |
|---|------------------------------------|
| <b>Brushless Motor</b>                    | YES                                |
| <b>Sound Pressure Level</b>               | 85 dB(A)                           |
| <b>Vibration Uncertainty (K Factor)</b>   | 1,5 m/s <sup>2</sup>               |
| <b>Driving Shank</b>                      | 1/2"-20UNF "                       |
| <b>Product Dimensions (L x W x H):</b>    | 182 x 86 x 282 mm                  |
| <b>Max. fastening torque Hard/Soft</b>    | 140 / 68 Nm                        |
| <b>Impacts per Minute (IPM)</b>           | 0 - 9750 / 39000 min <sup>-1</sup> |
| <b>System</b>                             | XGT 40Vmax/80V max                 |
| <b>Sound Power Level (L<sub>WA</sub>)</b> | 96 dB(A)                           |
| <b>Product net weight (new)</b>           | 1,7 kg                             |
| <b>Voltage XGT</b>                        | 1                                  |
| <b>Noise Uncertainty (K Factor)</b>       | 3 dB(A)                            |
| <b>Max. Drilling Diameter in Concrete</b> | 20 mm                              |
| <b>Max. Drilling Diameter in Masonry</b>  | 20 mm                              |
| <b>Drill Chuck Capacity</b>               | 1,5-13 mm                          |
| <b>Tool Category</b>                      | Screwing and Drilling              |
| <b>Electronic brake</b>                   | 1                                  |
| <b>No load speed</b>                      | 0 - 650 / 2600 min <sup>-1</sup>   |

### Standard Equipment

- ◎ 1pc DC40RA Fast Charger
- ◎ 2pcs x BL4040 (4.0Ah) 40V MAX XGT Battery
- ◎ Makpack Case

### More info

<https://makita.ae/product/percussion-driver-drill-xgt-hp001gm201/>