

## Percussion Driver Drill XGT HP002GA201

### Product Description

40V MAX XGT • 64 Nm • 0 - 2 200 min<sup>-1</sup>

#### **Rugged, brushless combi drill for heavy-duty screwdriving and drilling**

A powerful, brushless drill for professional screwdriving and drilling with or without hammer action, two power settings. Maximum torque of 64 / 30 Nm. An ideal choice for jobs that require high power and torque. Integrated LED light.



### Product Features

- ⊙ XPT (Extreme Protection Technology) is engineered for improved dust and water resistance for operation in harsh job site conditions
- ⊙ Brushless maintenance-free and long-life motor
- ⊙ Compact and lightweight design
- ⊙ Built-in LED job light illuminates the work area
- ⊙ Ergonomically designed handle with soft grip provides increased comfort on the job
- ⊙ Keyless chuck for easy bit installation and removal
- ⊙ Mechanical 2-speed gearing; High speed mode for speedy drilling in light duty applications; Low speed mode for heavy duty applications requiring high torque
- ⊙ Battery protection circuit protects against overloading, over-discharging and over-heating
- ⊙ Electric brake for maximum productivity
- ⊙ Reversing switch is conveniently located

### Barcode

88381735773

### Product Specifications

Drilling Capacity Wood (Auger Bit)	38 mm
Vibration Level (3 axes), Drilling	≤ 2,5 m/s <sup>2</sup>
Torque setting	21
Drilling Capacity Wood (Self-feed bit)	51 mm
Tool weight with battery (EPTA)	2,0 - 3,4 kg

<b>Max. Drilling Diameter in Steel</b>	13 mm
<b>Max. Drilling Diameter in Wood</b>	38 mm
<b>Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)</b>	Li-ion
<b>Vibration Level (3 axes), Impact Drilling</b>	9,0 m/s <sup>2</sup>
<b>Battery Voltage</b>	40 V
<b>Brushless Motor</b>	YES
<b>Sound Pressure Level</b>	87 dB(A)
<b>Vibration Uncertainty (K Factor)</b>	1,5 m/s <sup>2</sup>
<b>Driving Shank</b>	1/2"-20UNF "
<b>Product Dimensions (L x W x H):</b>	174 x 86 x 272 mm
<b>Max. fastening torque Hard/Soft</b>	64 / 30 Nm
<b>Impacts per Minute (IPM)</b>	0 - 9 000 / 33000 min <sup>-1</sup>
<b>System</b>	XGT 40Vmax/80V max
<b>Sound Power Level (L<sub>WA</sub>)</b>	98 dB(A)
<b>Product net weight (new)</b>	1,3 kg
<b>Voltage XGT</b>	1
<b>Noise Uncertainty (K Factor)</b>	3 dB(A)
<b>Max. Drilling Diameter in Concrete</b>	13 mm
<b>Max. Drilling Diameter in Masonry</b>	13 mm
<b>Drill Chuck Capacity</b>	1,5-13 mm
<b>Tool Category</b>	Screwing and Drilling
<b>Electronic brake</b>	1
<b>No load speed</b>	0 - 600 / 2200 min <sup>-1</sup>

#### Standard Equipment

- ⊙ 1pc DC40RA Fast Charger
- ⊙ 2pcs x BL4020 (2.0Ah) 40V MAX XGT Battery
- ⊙ Makpack Case

#### More info

<https://makita.ae/product/percussion-driver-drill-xgt-hp002ga201/>