

Percussion Driver Drill XGT HP002GZ



Product Description

40V MAX XGT • 64 Nm • 0 - 2 200 min⁻¹

Rugged, brushless combi drill for heavy-duty screwdriving and drilling

A powerful, brushless drill for professional screwdriving and drilling with or without hammer action, two power settings. Maximum torque of 64 / 30 Nm. An ideal choice for jobs that require high power and torque. Integrated LED light.

Product Features

- ⊙ XPT (Extreme Protection Technology) is engineered for improved dust and water resistance for operation in harsh job site conditions
- ⊙ Brushless maintenance-free and long-life motor
- ⊙ Compact and lightweight design
- ⊙ Built-in LED job light illuminates the work area
- ⊙ Ergonomically designed handle with soft grip provides increased comfort on the job
- ⊙ Keyless chuck for easy bit installation and removal
- ⊙ Mechanical 2-speed gearing; High speed mode for speedy drilling in light duty applications; Low speed mode for heavy duty applications requiring high torque
- ⊙ Battery protection circuit protects against overloading, over-discharging and over-heating
- ⊙ Electric brake for maximum productivity
- ⊙ Reversing switch is conveniently located

Barcode

88381735667

Product Specifications

| | |
|---|------------------------|
| Drilling Capacity Wood (Auger Bit) | 38 mm |
| Vibration Level (3 axes), Drilling | ≤ 2,5 m/s ² |
| Torque setting | 21 |
| Drilling Capacity Wood (Self-feed bit) | 51 mm |

| | |
|---|-------------------------------------|
| Tool weight with battery (EPTA) | 2,0 - 3,4 kg |
| Max. Drilling Diameter in Steel | 13 mm |
| Max. Drilling Diameter in Wood | 38 mm |
| Battery Chemistry (Ni-Cd / Ni-MH / Li-ion) | Li-ion |
| Vibration Level (3 axes), Impact Drilling | 9,0 m/s ² |
| Battery Voltage | 40 V |
| Brushless Motor | YES |
| Sound Pressure Level | 87 dB(A) |
| Vibration Uncertainty (K Factor) | 1,5 m/s ² |
| Driving Shank | 1/2"-20UNF " |
| Product Dimensions (L x W x H): | 174 x 86 x 272 mm |
| Max. fastening torque Hard/Soft | 64 / 30 Nm |
| Impacts per Minute (IPM) | 0 - 9 000 / 33000 min ⁻¹ |
| System | XGT 40Vmax/80V max |
| Sound Power Level (L_{WA}) | 98 dB(A) |
| Product net weight (new) | 1,3 kg |
| Voltage XGT | 1 |
| Noise Uncertainty (K Factor) | 3 dB(A) |
| Max. Drilling Diameter in Concrete | 13 mm |
| Max. Drilling Diameter in Masonry | 13 mm |
| Drill Chuck Capacity | 1,5-13 mm |
| Tool Category | Screwing and Drilling |
| Electronic brake | 1 |
| No load speed | 0 - 600 / 2200 min ⁻¹ |

Standard Equipment

⊙ Sold without Battery or Charger

More info

<https://makita.ae/product/percussion-driver-drill-xgt-hp002gz/>