

Plunge Cut Saw SP6000



Product Description

1 300 W • 2 200 - 6 400 min⁻¹ • 165 mm

Precise plunge cut circular saw

A precise plunge cut circular saw for accurate cutting. Ideal for installing furnishing or decking. Recommended for use with a guide rail. A motor capacity of 1 300 W and cutting capacity of 56mm. Speed can be adjusted between 2 200 - 6 400 min⁻¹.

Product Specifications

Bore Size (Arbor Diameter)	20 mm
Max. Cutting Depth at 45°	40 mm
Sound Pressure Level	92 dB(A)
Power Supply Cord	2,5 m
Continuous Input Power	1300 W
Vibration Uncertainty (K Factor)	1,5 m/s ²
Product Dimensions (L x W x H):	341 x 225 x 250 mm
Product net weight (new)	4,1 kg
Vibration Level (3 axes)	≤ 2,5 m/s ²
Sound Power Level (L_{WA})	103 dB(A)
Max. Cutting Depth at 90°	56 mm
Blade Diameter	165 mm
Weight Without Cable (EPTA)	4,1 kg
Noise Uncertainty (K Factor)	3 dB(A)
Vacuum cleaner connection Ø in / out	35/43 mm
Max. Cutting Depth at 48°	38 mm
Tool Category	Sawing
No load speed	2200 - 6400 min ⁻¹

More info

<https://makita.ae/product/plunge-cut-saw-sp6000/>