



Plunge Router RP2300FC



Product Description

2 300 W • 12 mm

Powerful professional plunge router

A powerful plunge router with a 2 300 W motor for professional use. Equipped with depth adjustment with micro control and an LED job light. 12 mm and 8 mm collets. Suitable for use as a fixed base router. Guide with micro control included.

Product Features

- LED light illuminates the work site

Barcode

88381099424

Product Specifications

| | |
|---|--------------------------------|
| Base dimensions | 170 x 155 mm |
| Max. Collet Capacity | 12 mm |
| Sound Pressure Level | 87 dB(A) |
| Power Supply Cord | 4,0 m |
| Continuous Input Power | 2300 W |
| Vibration Uncertainty (K Factor) | 1,5 m/s ² |
| Product Dimensions (L x W x H): | 155 x 294 x 312 mm |
| Product net weight (new) | 6,1 kg |
| Vibration Level (3 axes) | 4,5 m/s ² |
| Sound Power Level (L_{WA}) | 98 dB(A) |
| Weight Without Cable (EPTA) | 6,1 kg |
| Noise Uncertainty (K Factor) | 3 dB(A) |
| Vacuum cleaner connection Ø in / out | 32/37 mm |
| Plunge capacity | 0 - 70 mm |
| Tool Category | Milling and Planing |
| No load speed | 9000 - 22000 min ⁻¹ |

More info

<https://makita.ae/product/plunge-router-rp2300fc/>