



## Pneumatic Brad Nailer AF506



### Product Description

15 - 50 mm • 18 Ga

#### Pneumatic Brad nailer with depth adjustment for finishing

For finishing nails such as panel, strip, joint and stacking nails. The narrow mouthpiece of the nailer is suitable, for example, for concealed and tongue nailing. The rubber cuff prevents dents. The nailer uses 1.2 mm countersunk head nails, which can be 15 - 50 mm long.

### Product Features

- ◎ The rubber coating on the handle ensures a firm working grip

### Barcode

88381870733

### Product Specifications

<b>Plastic Carrying Case</b>	1
<b>Magazine Angle</b>	0 °
<b>Operating pressure</b>	4,9 - 8,3 bar
<b>Depth Adjustment</b>	1
<b>Fastener Gauge</b>	18 Ga
<b>Product Dimensions (L x W x H):</b>	250 x 70 x 256 mm
<b>Sound Pressure Level</b>	99 dB(A)
<b>Nail Length</b>	15 - 50 mm
<b>Vibration Uncertainty (K Factor)</b>	1,5 m/s <sup>2</sup>
<b>Noise Uncertainty (K Factor)</b>	1,5 dB(A)
<b>Fastener Magazine Capacity</b>	100
<b>Tool Category</b>	Fastening and Fixing
<b>Nail Diameter</b>	1,2 mm
<b>Sound Power Level (L<sub>WA</sub>)</b>	109 dB(A)
<b>Vibration Level (3 axes)</b>	7,6 m/s <sup>2</sup>
<b>Product net weight (new)</b>	1,3 kg

### More info

<https://makita.ae/product/pneumatic-brad-nailer-af506/>