

Pneumatic Brad Nailer

AF506



Product Description

15 - 50 mm • 18 Ga

Pneumatic Brad nailer with depth adjustment for finishing

For finishing nails such as panel, strip, joint and stacking nails. The narrow mouthpiece of the nailer is suitable, for example, for concealed and tongue nailing. The rubber cuff prevents dents. The nailer uses 1.2 mm countersunk head nails, which can be 15 - 50 mm long.

Product Features

- ⦿ The rubber coating on the handle ensures a firm working grip

Barcode

88381870733

Product Specifications

Plastic Carrying Case	1
Magazine Angle	0 °
Operating pressure	4,9 - 8,3 bar
Depth Adjustment	1
Fastener Gauge	18 Ga
Product Dimensions (L x W x H):	250 x 70 x 256 mm
Sound Pressure Level	99 dB(A)
Nail Length	15 - 50 mm
Vibration Uncertainty (K Factor)	1,5 m/s ²
Noise Uncertainty (K Factor)	1,5 dB(A)
Fastener Magazine Capacity	100
Tool Category	Fastening and Fixing
Nail Diameter	1,2 mm
Sound Power Level (L _{WA})	109 dB(A)
Vibration Level (3 axes)	7,6 m/s ²
Product net weight (new)	1,3 kg

More info

<https://makita.ae/product/pneumatic-brad-nailer-af506/>