

# **Pneumatic Coil Nailer**

# **AN613**



## **Product Description**

38 - 65 mm

## **Heavy-duty nailer**

A compact siding coil nailer for construction and packing applications and installing wood shingle. Options for depth adjustment and sequential and contact nailing. No need for continuous hose lubrication.

#### **Product Features**

- Building and packaging boards, and other demanding nailing applications such as outdoor paneling.
- External wire nailer for iron wire (max 65mm) and plastic binding nails (max 50mm).
- Depth adjustment
- Supply air filtration
- Trend of exhaust air.

Product Specifications

## Barcode

88381897525

Troduct Specifications	
Magazine Angle	15 º
Operating pressure	4,4 - 8,3 bar
Depth Adjustment	1
Product Dimensions (L x W x H):	275 x 127 x 319 mm

Product Dimensions (L x w x H):	2/5 X 12/ X 319 mm
Sound Pressure Level	116 dB(A)
Nail Length	38 - 65 mm
Vibration Uncertainty (K Factor)	1,5 m/s <sup>2</sup>
Noise Uncertainty (K Factor)	1,5 dB(A)
Fastener Magazine Capacity	200 - 300
Tool Category	Fastening and Fixing
Nail Diameter	2,3-2,5 mm
Sound Power Level (L <sub>WA</sub> )	130 dB(A)
Vibration Level (3 axes)	3,0 m/s <sup>2</sup>

2,2 kg

#### More info

Product net weight (new)