

Pneumatic Coil Nailer

AN613



Product Description

38 - 65 mm

Heavy-duty nailer

A compact siding coil nailer for construction and packing applications and installing wood shingle. Options for depth adjustment and sequential and contact nailing. No need for continuous hose lubrication.

Product Features

- ⊙ Building and packaging boards, and other demanding nailing applications such as outdoor paneling.
- ⊙ External wire nailer for iron wire (max 65mm) and plastic binding nails (max 50mm).
- ⊙ Depth adjustment
- ⊙ Supply air filtration
- ⊙ Trend of exhaust air.

Barcode

88381897525

Product Specifications

| | |
|---|----------------------|
| Magazine Angle | 15 ° |
| Operating pressure | 4,4 - 8,3 bar |
| Depth Adjustment | 1 |
| Product Dimensions (L x W x H): | 275 x 127 x 319 mm |
| Sound Pressure Level | 116 dB(A) |
| Nail Length | 38 - 65 mm |
| Vibration Uncertainty (K Factor) | 1,5 m/s ² |
| Noise Uncertainty (K Factor) | 1,5 dB(A) |
| Fastener Magazine Capacity | 200 - 300 |
| Tool Category | Fastening and Fixing |
| Nail Diameter | 2,3-2,5 mm |
| Sound Power Level (L_{WA}) | 130 dB(A) |
| Vibration Level (3 axes) | 3,0 m/s ² |
| Product net weight (new) | 2,2 kg |

More info

<https://makita.ae/product/pneumatic-coil-nailer-an613/>