

Portable Band Saw LXT DPB183Z



Product Description

18V LXT • 66 mm • 0 - 3.2 m/s

Safe, non-sparking metal cutting

Cordless band saw for non-sparking metal cutting. Sawing capacity 66 x 66 mm. Brushless motor with adjustable speed 0–3.2 m / s. Sturdy and torsionally rigid aluminum frame ensures straight saws. Tool only, battery and charger not included.

Product Features

- ⊙ LED light illuminates the work site
- ⊙ The rubber coating on the handle ensures a firm working grip
- ⊙ Cutting metal quickly and without sparks.
- ⊙ Brushless maintenance-free and long-life motor
- ⊙ Battery protection system automatically shuts off power when the battery level is low
- ⊙ The standard electronics keep the speed constant even under load.
- ⊙ Variable speed trigger allows operator to adjust speed based on materials or application

Barcode

88381899697

Product Specifications

| | |
|--|------------------------|
| Battery Chemistry (Ni-Cd / Ni-MH / Li-ion) | Li-ion |
| Tool weight with battery (EPTA) | 3,6 - 3,9 kg |
| Blade rapidity | 0 - 3,2 m/s |
| Cutting Capacity Mild Steel (up to 400N/mm²) | 66 x 66 mm |
| Brushless Motor | YES |
| Battery Voltage | 18 V |
| Sound Pressure Level | 80 dB(A) |
| Product Dimensions (L x W x H): | 392 x 174 x 242 mm |
| Vibration Level (3 axes) | ≤ 2,5 m/s ² |
| Sound Power Level (L_{sub}&gt;WA_{sub}&gt;) | 90 dB(A) |
| Voltage LXT | 1 |
| System | LXT 18V/36V |
| Product net weight (new) | 3,3 kg |
| Vibration Uncertainty (K Factor) | 1,5 m/s ² |
| Max. Log Diameter | 66 mm |
| Noise Uncertainty (K Factor) | 3 dB(A) |
| Blade Size | 13 x 0,5 x 835 mm |
| Tool Category | Sawing |

| | |
|--|-------|
| Max. Cutting Capacity in Steel Pipe | 66 mm |
|--|-------|

Standard Equipment

⦿ Sold without Battery or Charger

More info

<https://makita.ae/product/portable-band-saw-lxt-dpb183z/>