

Portable Band Saw LXT

DPB183Z



Product Description

18V LXT • 66 mm • 0 - 3.2 m/s

Safe, non-sparking metal cutting

Cordless band saw for non-sparking metal cutting. Sawing capacity 66×66 mm. Brushless motor with adjustable speed 0-3.2 m/s. Sturdy and torsionally rigid aluminum frame ensures straight saws. Tool only, battery and charger not included.

Product Features

- LED light illuminates the work site
- The rubber coating on the handle ensures a firm working grip
- Cutting metal quickly and without sparks.
- Brushless maintenance-free and long-life motor
- Battery protection system automatically shuts off power when the battery level is low
- The standard electronics keep the speed constant even under load.
- Variable speed trigger allows operator to adjust speed based on materials or application

Barcode

88381899697

| _ | | _ | | | |
|------|-------|-----|------|-----|------|
| Prod | liict | Sne | CITI | cat | inns |

| 1 Todact Specifications | |
|----------------------------------------------|----------------------|
| Battery Chemistry (Ni-Cd / Ni-MH / Li-ion) | Li-ion |
| Tool weight with battery (EPTA) | 3,6 - 3,9 kg |
| Blade rapidity | 0 - 3,2 m/s |
| Cutting Capacity Mild Steel (up to 400N/mm²) | 66 x 66 mm |
| Brushless Motor | YES |
| Battery Voltage | 18 V |
| Sound Pressure Level | 80 dB(A) |
| Product Dimensions (L x W x H): | 392 x 174 x 242 mm |
| Vibration Level (3 axes) | ≤ 2,5 m/s² |
| Sound Power Level (L&Itsub>WA&It/sub>) | 90 dB(A) |
| Voltage LXT | 1 |
| System | LXT 18V/36V |
| Product net weight (new) | 3,3 kg |
| Vibration Uncertainty (K Factor) | 1,5 m/s ² |
| Max. Log Diameter | 66 mm |
| Noise Uncertainty (K Factor) | 3 dB(A) |
| Blade Size | 13 x 0,5 x 835 mm |
| Tool Category | Sawing |

| - | | |
|---|-------------------------------------|-------|
| | Max. Cutting Capacity in Steel Pipe | 66 mm |

Standard Equipment

Sold without Battery or Charger

More info

https://makita.ae/product/portable-band-saw-lxt-dpb183z/