

## Random Orbit Polisher LXT DPO600RTE



### Product Description

LXT • 18V LXT • 780 min<sup>-1</sup> • 150 mm

#### Random Orbit Polisher LXT for professionals

Normal mode is orbital action with forced rotation of the pad for rough polishing such as surface treatment. Finishing mode is orbital action with free rotation of the pad for fine polishing; allows 30 min. operation with 18V 6.0 Ah Li-ion battery. Damage guards for car body. Includes 2 x 5,0 Ah batteries and a charger.

### Product Features

- ⊙ Battery protection system automatically shuts off power when the battery level is low

### Barcode

88381871815

### Product Specifications

<b>Sanding Orbit Diameter</b>	5,5 mm
<b>Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)</b>	Li-ion
<b>Tool weight with battery (EPTA)</b>	3,1 - 3,6 kg
<b>Brushless Motor</b>	YES
<b>Battery Voltage</b>	18 V
<b>Sound Pressure Level</b>	83 dB(A)
<b>Product Dimensions (L x W x H):</b>	530 x 148 x 126 mm
<b>Strokes per Minute (SPM)</b>	0 - 10400 / 13600 min <sup>-1</sup>
<b>Sound Power Level (L<sub>WA</sub>)</b>	94 dB(A)
<b>Voltage LXT</b>	1
<b>System</b>	LXT 18V/36V
<b>Product net weight (new)</b>	2,6 kg
<b>Vibration Uncertainty (K Factor)</b>	1,5 m/s <sup>2</sup>
<b>Noise Uncertainty (K Factor)</b>	3 dB(A)
<b>Tool Category</b>	Grinding, Sanding and Polishing
<b>Sanding Disc Diameter</b>	150 mm
<b>Orbits per Minute</b>	0-6800 min <sup>-1</sup>
<b>No load speed</b>	0 - 600 / 0 - 780 min <sup>-1</sup>
<b>Vibration Level (3 axes), Polishing</b>	10,0 m/s <sup>2</sup>

### Standard Equipment

- ⊙ 1pc DC18RC Fast Charger
- ⊙ 2pcs BL1850B (5.0Ah) 18V LXT Battery
- ⊙ Carry Case

More info

<https://makita.ae/product/random-orbit-polisher-lxt-dpo600rte/>