

Random Orbit Sander

BO6050J



Product Description

750 W • 150 mm

Efficient tool with reliable rotation under load

A sander with random orbit and random orbit with forced rotation actions for a wide range of applications. Through-the-pad dust collection. Pad diameter of 150 mm. Comes in a Makpac case.

Product Features

- ⦿ The rubber coating on the handle ensures a firm working grip
- ⦿ fits perfectly as a polish machine
- ⦿ 2 settings for polishing and polishing

Barcode

88381804592

Product Specifications

| | |
|--------------------------------------|---------------------------------|
| Sanding pad diameter | 150 mm |
| Sanding Orbit Diameter | 5,5 mm |
| Power Supply Cord | 2,5 m |
| Product Dimensions (L x W x H): | 330 x 155 x 145 mm |
| Sound Pressure Level | 82 dB(A) |
| Sanding Disc Diameter | 150 mm |
| Orbits per Minute | 1600-6800 min ⁻¹ |
| Vibration Uncertainty (K Factor) | 1,5 m/s ² |
| Continuous Input Power | 750 W |
| Weight Without Cable (EPTA) | 2,6 kg |
| Noise Uncertainty (K Factor) | 3 dB(A) |
| Vacuum cleaner connection Ø in / out | 23/28 mm |
| Tool Category | Grinding, Sanding and Polishing |
| Vibration Level (3 axes) | 5,0 m/s ² |
| Sound Power Level (L _{WA}) | 93 dB(A) |

More info

<https://makita.ae/product/random-orbit-sander-bo6050j/>