

## Rear Handle Circular Saw LXT

# DRS780Z



### Product Description

36V (18Vx2) LXT • 5 100 min<sup>-1</sup> • 185 mm

#### **Robust brushless professional saw with remote start for vacuum**

A robust brushless saw with remote start for dust extraction, designed for cutting wood. Two LXT 18V batteries offer an output of 18V+18V. Accepts blades with 185 mm diameter that achieve a max. cutting depth of 65 mm. Tool only, battery and charger not included. Tool only, battery and charger not included.

### Product Features

- ⊙ The safety switch prevents accidental start-up of the tool
- ⊙ Battery protection system automatically shuts off power when the battery level is low
- ⊙ The rubber coating on the handle ensures a firm working grip
- ⊙ Body model - delivered without battery and charger.

### Barcode

88381838665

### Product Specifications

<b>Bore Size (Arbor Diameter)</b>	20 / 30 mm
<b>Max. Cutting Depth at 45°</b>	45 mm
<b>Capacity 45° (Miter R/L 45°, Bevel 0°)</b>	45 mm
<b>Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)</b>	Li-ion
<b>Tool weight with battery (EPTA)</b>	5,0 - 5,6 kg
<b>Brushless Motor</b>	YES
<b>Battery Voltage</b>	2 x 18 V
<b>Max. Bevel Range (Left)</b>	0 / 53 °
<b>Sound Pressure Level</b>	92 dB(A)
<b>Product Dimensions (L x W x H):</b>	446 x 196 x 270 mm
<b>Vibration Level (3 axes)</b>	≤ 2,5 m/s <sup>2</sup>
<b>Sound Power Level (L<sub>WA</sub>)</b>	103 dB(A)
<b>Voltage LXT</b>	1
<b>System</b>	LXT 18V/36V
<b>Product net weight (new)</b>	4,3 kg
<b>Vibration Uncertainty (K Factor)</b>	1,5 m/s <sup>2</sup>
<b>Noise Uncertainty (K Factor)</b>	3 dB(A)
<b>Tool Category</b>	Sawing
<b>Blade Diameter</b>	185 mm
<b>Max. Cutting Depth at 90°</b>	65 mm
<b>Max Output Power</b>	1700 W

<b>No load speed</b>	5100 min <sup>-1</sup>
----------------------	------------------------

Standard Equipment

⦿ Sold without Battery or Charger

More info

<https://makita.ae/product/rear-handle-circular-saw-lxt-drs780z/>