

Rear Handle Circular Saw XGT

RS002GT101



Product Description

40V MAX XGT • 260mm

Highly robust circular saw for demanding applications

40V max XGT® Li-ion battery and brushless motor makes this saw excellent choice for demanding applications. The blade can reach up to 4 000 min⁻¹ to ensure high cutting performance with large cutting capacity. Vacuum remote startup function (AWS) and XPT for improved dust and water resistance.

Product Features

- ⊙ Electric motor brake
- ⊙ Soft start provides safety when working.
- ⊙ XPT (Extreme Protection Technology) is engineered for improved dust and water resistance for operation in harsh job site conditions
- ⊙ Retractable, extra-wide tool hook secures the tool when not in use
- ⊙ Auto-start Wireless System (AWS) connects to compatible vacuum cleaners with Bluetooth
- ⊙ Battery protection circuit protects against overloading, over-discharging and over-heating

Barcode

88381737661

Product Specifications

Max. Cutting Depth at 56°	54,5 mm
Tool weight with battery (EPTA)	5,7 - 6,9 kg
Bore Size (Arbor Diameter)	30 mm
Max. Cutting Depth at 45°	70 mm
Capacity 45° (Miter R/L 45°, Bevel 0°)	70 mm
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
Battery Voltage	40 V
Brushless Motor	YES
Sound Pressure Level	96 dB(A)
Max. Bevel Range (Left)	0 / 56 °
Continuous Input Power	1700 W
Vibration Uncertainty (K Factor)	1,5 m/s ²
Product Dimensions (L x W x H):	489 x 193 x 309 mm
Product net weight (new)	5,0 kg
System	XGT 40Vmax/80V max
Vibration Level (3 axes)	≤ 2,5 m/s ²
Sound Power Level (L _{WA})	107 dB(A)
Blade Diameter	260 mm
Max. Cutting Depth at 90°	95 mm

Voltage XGT	1
Noise Uncertainty (K Factor)	3 dB(A)
Vacuum cleaner connection Ø in / out	30/37 mm
Tool Category	Sawing
AWS FUNCTION	YES
No load speed	4000 min ⁻¹

Standard Equipment

- ⊙ 1pc DC40RA Fast Charger
- ⊙ 1pc x BL4050F (5.0Ah) 40V MAX XGT Battery
- ⊙ Makpac Case

More info

<https://makita.ae/product/rear-handle-circular-saw-xgt-rs002gt101/>