



## Rebar Tying Tool XGT TR001GZ



### Product Description

40V MAX XGT • BL Motor

#### Excellent Combination of High Tying Strength and Speed

TR001G is the very first Cordless Rebar Tying Tool in 40V MAX XGT range

By adopting a high-voltage XGT battery and ø1.6mm thick wire, the tool delivers high tying strength and speed.

Comes without Battery and Charger.

[▶ Watch Product Video](#)

### Product Features

- ◎ Equipped with a wire pullback mechanism, TR001G pulls back the wire while holding its tip, allowing the rebars to be tightly and securely tied
- ◎ Dual Brushless (BL) Motors - One for twisting and One for feeding the wire. This improves stability when using thicker wire
- ◎ Accepts thicker tie wire - Annealed wire of 1.6 mm diameter (Ø16 Ga) compared to 0.8 mm in the current LXT model
- ◎ One-step Wire Reel Loading - Improved mechanism with linked cover & gear so the reel change / loading is faster
- ◎ Clockwise Wire Twisting - Designed to reduce the chance of unintentional loosening if someone retightens by hand
- ◎ 6-stage adjustable tying strength: lets you match the tying force to the combination of rebar sizes / conditions

### Product Specifications

<b>Applicable Rebar for Tying</b>	D10 x D10 - (D16 x 2) x (D16 x 2)
<b>Applicable Tie Wire</b>	Annealed Wire: 16Ga (1.6 mm)
<b>Tying Speed</b>	0.7 s
<b>Tying Strength Adjustment</b>	6 Stages
<b>Number of Ties</b>	Per Reel: 240 / On a full battery charge (BL4040): 3,900
<b>Wire Tail Height</b>	16 mm (5/8")
<b>Nose Width</b>	5.6 mm (7/32")
<b>Dimensions (L x W x H)</b>	375 x 113 x 331 mm
<b>Net Weight</b>	2.6 kg (without battery)

### Standard Equipment

- ◎ Hex Wrench

- ◎ Hook
- ◎ Oil Supply

More info

<https://makita.ae/product/rebar-tying-tool-xgt-tr001gz/>