



# Reciprocating Saw AC JR3061T



## Product Description

1 250 W • 0 – 3 000 min<sup>-1</sup> • 32 mm

### Rugged reciprocating saw with three-stage pendulum action

A basic reciprocating saw for spark-free cutting of metal and demolition work. An efficient 1 250 W motor, stroke length of 32 mm and stroke rate of 0 – 3 000 min<sup>-1</sup> with continuous control from the switch. Three-stage pendulum action and quick-release blade attachment.

## Product Specifications

<b>Power Supply Cord UK</b>	2,5 m
<b>Vibration Level (3 axes), Cutting Wood</b>	16,5 m/s <sup>2</sup>
<b>Max. Cutting Capacity in Wood (90°)</b>	255 mm
<b>Sound Pressure Level</b>	88 dB(A)
<b>Vibration Level (3 axes), Cutting Chipboard</b>	18,5 m/s <sup>2</sup>
<b>Power Supply Cord</b>	4,0 m
<b>Length of Stroke</b>	32 mm
<b>Product Dimensions (L x W x H):</b>	487 x 95 x 177 mm
<b>Strokes per Minute (SPM)</b>	0 - 3000 min <sup>-1</sup>
<b>Continuous Input Power</b>	1250 W
<b>Vibration Uncertainty (K Factor)</b>	1,5 m/s <sup>2</sup>
<b>Product net weight (new)</b>	3,8 kg
<b>Vibration Level (3 axes)</b>	18,5 m/s <sup>2</sup>
<b>Sound Power Level (L<sub>WA</sub>)</b>	99 dB(A)
<b>Weight Without Cable (EPTA)</b>	3,8 kg
<b>Noise Uncertainty (K Factor)</b>	3 dB(A)
<b>Max. Cutting Capacity in Steel Pipe</b>	130 mm
<b>Tool Category</b>	Sawing

## More info

<https://makita.ae/product/reciprocating-saw-ac-jr3061t/>