

## Reciprocating Saw AC JR3061T



### Product Description

1 250 W • 0 - 3 000 min<sup>-1</sup> • 32 mm

#### **Rugged reciprocating saw with three-stage pendulum action**

A basic reciprocating saw for spark-free cutting of metal and demolition work. An efficient 1 250 W motor, stroke length of 32 mm and stroke rate of 0 - 3 000 min<sup>-1</sup> with continuous control from the switch. Three-stage pendulum action and quick-release blade attachment.

### Product Specifications

Power Supply Cord UK	2,5 m
Vibration Level (3 axes), Cutting Wood	16,5 m/s <sup>2</sup>
Max. Cutting Capacity in Wood (90°)	255 mm
Sound Pressure Level	88 dB(A)
Vibration Level (3 axes), Cutting Chipboard	18,5 m/s <sup>2</sup>
Power Supply Cord	4,0 m
Length of Stroke	32 mm
Product Dimensions (L x W x H):	487 x 95 x 177 mm
Strokes per Minute (SPM)	0 - 3000 min <sup>-1</sup>
Continuous Input Power	1250 W
Vibration Uncertainty (K Factor)	1,5 m/s <sup>2</sup>
Product net weight (new)	3,8 kg
Vibration Level (3 axes)	18,5 m/s <sup>2</sup>
Sound Power Level (L <sub>WA</sub> )	99 dB(A)
Weight Without Cable (EPTA)	3,8 kg
Noise Uncertainty (K Factor)	3 dB(A)
Max. Cutting Capacity in Steel Pipe	130 mm
Tool Category	Sawing

### More info

<https://makita.ae/product/reciprocating-saw-ac-jr3061t/>