

## Reciprocating Saw CXT JR105DZ



### Product Description

12V MAX • 0 - 3 300 min<sup>-1</sup> • 13 mm

**Compact reciprocating saw for light use, also accepts jigsaw bits**

A straight-framed light and small reciprocating saw offers access to tight places. Two separate switches enable diverse working postures. Stroke length of 13 mm, stroke rate can be adjusted between 0 - 3 300 min<sup>-1</sup> from a switch. LED light. Tool only, battery and charger not included.

### Product Features

- ⊙ LED light illuminates the work site
- ⊙ The rubber coating on the handle ensures a firm working grip
- ⊙ Body model - delivered without battery and charger.
- ⊙ Battery protection system automatically shuts off power when the battery level is low

### Barcode

88381800907

### Product Specifications

<b>Vibration Level (3 axes), Cutting Wood</b>	8,0 m/s <sup>2</sup>
<b>Tool weight with battery (EPTA)</b>	1,3 - 1,5 kg
<b>Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)</b>	Li-ion
<b>Battery Voltage</b>	12 V
<b>Max. Cutting Capacity in Wood (90°)</b>	50 mm
<b>Sound Pressure Level</b>	81 dB(A)
<b>CXT Battery</b>	1
<b>Vibration Level (3 axes), Cutting Chipboard</b>	8,0 m/s <sup>2</sup>
<b>Length of Stroke</b>	13 mm
<b>Product Dimensions (L x W x H):</b>	376 x 66 x 186 mm
<b>Strokes per Minute (SPM)</b>	0 - 3300 min <sup>-1</sup>
<b>Vibration Uncertainty (K Factor)</b>	1,5 m/s <sup>2</sup>
<b>Product net weight (new)</b>	1,1 kg
<b>System</b>	CXT 12Vmax
<b>Vibration Level (3 axes)</b>	8,0 m/s <sup>2</sup>
<b>Sound Power Level (L<sub>WA</sub>)</b>	89 dB(A)
<b>Noise Uncertainty (K Factor)</b>	3 dB(A)
<b>Max. Cutting Capacity in Steel Pipe</b>	50 mm
<b>Tool Category</b>	Sawing

### Standard Equipment

- ⊙ Sold without Battery or Charger

More info

<https://makita.ae/product/reciprocating-saw-cxt-jr105dz/>