

### **Reciprocating Saw CXT**

## JR105DZ



#### **Product Description**

12V MAX • 0 - 3 300 min<sup>-1</sup> • 13 mm

# Compact reciprocating saw for light use, also accepts jigsaw bits

A straight-framed light and small reciprocating saw offers access to tight places. Two separate switches enable diverse working postures. Stroke length of 13 mm, stroke rate can be adjusted between 0 – 3 300 min-1 from a switch. LED light. Tool only, battery and charger not included.

#### **Product Features**

- LED light illuminates the work site
- The rubber coating on the handle ensures a firm working grip
- Body model delivered without battery and charger.
- Battery protection system automatically shuts off power when the battery level is low

#### Barcode

88381800907

Product Specifications	
Vibration Level (3 axes), Cutting Wood	8,0 m/s <sup>2</sup>
Tool weight with battery (EPTA)	1,3 - 1,5 kg
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
Battery Voltage	12 V
Max. Cutting Capacity in Wood (90°)	50 mm
Sound Pressure Level	81 dB(A)
CXT Battery	1
Vibration Level (3 axes), Cutting Chipboard	8,0 m/s <sup>2</sup>
Length of Stroke	13 mm
Product Dimensions (L x W x H):	376 x 66 x 186 mm
Strokes per Minute (SPM)	0 - 3300 min <sup>-1</sup>
Vibration Uncertainty (K Factor)	1,5 m/s <sup>2</sup>
Product net weight (new)	1,1 kg
System	CXT 12Vmax
Vibration Level (3 axes)	8,0 m/s²
Sound Power Level (L <sub>WA</sub> )	89 dB(A)
Noise Uncertainty (K Factor)	3 dB(A)
Max. Cutting Capacity in Steel Pipe	50 mm
Tool Category	Sawing

#### Standard Equipment

## More info

https://makita.ae/product/reciprocating-saw-cxt-jr105dz/