

Reciprocating Saw CXT

JR105DZ



Product Description

12V MAX • 0 - 3 300 min⁻¹ • 13 mm

Compact reciprocating saw for light use, also accepts jigsaw bits

A straight-framed light and small reciprocating saw offers access to tight places. Two separate switches enable diverse working postures. Stroke length of 13 mm, stroke rate can be adjusted between 0 - 3 300 min⁻¹ from a switch. LED light. Tool only, battery and charger not included.

Product Features

- ◉ LED light illuminates the work site
- ◉ The rubber coating on the handle ensures a firm working grip
- ◉ Body model - delivered without battery and charger.
- ◉ Battery protection system automatically shuts off power when the battery level is low

Barcode

88381800907

Product Specifications

Vibration Level (3 axes), Cutting Wood	8,0 m/s ²
Tool weight with battery (EPTA)	1,3 - 1,5 kg
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
Battery Voltage	12 V
Max. Cutting Capacity in Wood (90°)	50 mm
Sound Pressure Level	81 dB(A)
CXT Battery	1
Vibration Level (3 axes), Cutting Chipboard	8,0 m/s ²
Length of Stroke	13 mm
Product Dimensions (L x W x H):	376 x 66 x 186 mm
Strokes per Minute (SPM)	0 - 3300 min ⁻¹
Vibration Uncertainty (K Factor)	1,5 m/s ²
Product net weight (new)	1,1 kg
System	CXT 12Vmax
Vibration Level (3 axes)	8,0 m/s ²
Sound Power Level (L _{WA})	89 dB(A)
Noise Uncertainty (K Factor)	3 dB(A)
Max. Cutting Capacity in Steel Pipe	50 mm
Tool Category	Sawing

Standard Equipment

- ◉ Sold without Battery or Charger

More info

<https://makita.ae/product/reciprocating-saw-cxt-jr105dz/>