

## Reciprocating Saw

# JR3051TK



### Product Description

1 200 W • 0 - 3 000 min<sup>-1</sup> • 30 mm

#### Reliable reciprocating saw for professionals

A basic reciprocating saw for spark-free cutting of metal and demolition work. An efficient 1 200 W motor, stroke length of 30 mm and stroke rate of 0 - 3 000 min<sup>-1</sup> with continuous control from the switch. Quick-release blade attachment.

### Product Features

- ⊙ Variable speed trigger for precise cutting in a wide variety of applications
- ⊙ Toolless blade change for fast blade installation and removal
- ⊙ Large 2-finger trigger for added convenience

### Barcode

88381891905

### Product Specifications

Power Supply Cord UK	2,5 m
Vibration Level (3 axes), Cutting Wood	19,5 m/s <sup>2</sup>
Max. Cutting Capacity in Wood (90°)	255 mm
Sound Pressure Level	88 dB(A)
Vibration Level (3 axes), Cutting Chipboard	19,5 m/s <sup>2</sup>
Power Supply Cord	4,0 m
Length of Stroke	30 mm
Product Dimensions (L x W x H):	447 x 97 x 176 mm
Strokes per Minute (SPM)	0 - 3000 min <sup>-1</sup>
Continuous Input Power	1200 W
Vibration Uncertainty (K Factor)	1,5 m/s <sup>2</sup>
Product net weight (new)	3,3 kg
Vibration Level (3 axes)	19,5 m/s <sup>2</sup>
Sound Power Level (L <sub>WA</sub> )	99 dB(A)
Weight Without Cable (EPTA)	3,3 kg
Noise Uncertainty (K Factor)	3 dB(A)
Max. Cutting Capacity in Steel Pipe	130 mm
Tool Category	Sawing

### More info

<https://makita.ae/product/reciprocating-saw-jr3051tk/>