

# Reciprocating Saw

## JR3070CT



### Product Description

1 510 W • 0 - 2 800 min<sup>-1</sup> • 32 mm

#### Rugged reciprocating saw with three-stage pendulum action and anti-vibration system

A professional reciprocating saw with AVT (anti-vibration technology) for spark-free cutting of metal and demolition work. An efficient 1 510 W motor, stroke length of 32 mm and stroke rate of 0 - 2 800 min<sup>-1</sup> with continuous control from the switch. Three-stage pendulum action and quick-release blade attachment.

### Product Features

- ⦿ AVT (Anti-Vibration Technology) ensures extra-low vibration performance
- ⦿ Lock-on feature for continuous operation
- ⦿ Variable speed trigger allows operator to adjust speed based on materials or application
- ⦿ Double insulated

### Barcode

88381061322

### Product Specifications

Vibration Level (3 axes), Cutting Wood	10,5 m/s <sup>2</sup>
Orbital Action	1
Max. Cutting Capacity in Wood (90°)	255 mm
Sound Pressure Level	88 dB(A)
Vibration Level (3 axes), Cutting Chipboard	9,5 m/s <sup>2</sup>
Power Supply Cord	2,5 m
Length of Stroke	32 mm
Product Dimensions (L x W x H):	485 x 99 x 181 mm
Strokes per Minute (SPM)	0 - 2800 min <sup>-1</sup>
Continuous Input Power	1510 W
Vibration Uncertainty (K Factor)	1,5 m/s <sup>2</sup>
Product net weight (new)	4,6 kg
Vibration Level (3 axes)	9,5 m/s <sup>2</sup>
Sound Power Level (L <sub>WA</sub> )	99 dB(A)
Weight Without Cable (EPTA)	4,4 kg
Noise Uncertainty (K Factor)	3 dB(A)
Max. Cutting Capacity in Steel Pipe	130 mm
Tool Category	Sawing

### More info

<https://makita.ae/product/reciprocating-saw-jr3070ct/>