

# Reciprocating Saw LXT

## DJR181RTE



### Product Description

18V LXT • 0 - 2 800 min<sup>-1</sup> • 28 mm

#### High speed for non-sparking metal cutting.

Reciprocating Saw with 18V voltage. High speed for non-sparking metal cutting. Tool change and blade adjustment without tool. Two 5.0Ah batteries and 36 min charger. Includes 2 x 5,0 Ah batteries and a charger in a case.

### Product Features

- ◉ LED light illuminates the work site
- ◉ Battery protection system automatically shuts off power when the battery level is low
- ◉ Body model - delivered without battery and charger.

### Barcode

88381693066

### Product Specifications

Vibration Level (3 axes), Cutting Wood	14,0 m/s <sup>2</sup>
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
Tool weight with battery (EPTA)	3,5 - 3,7 kg
Battery Voltage	18 V
Max. Cutting Capacity in Wood (90°)	255 mm
Sound Pressure Level	84 dB(A)
Vibration Level (3 axes), Cutting Chipboard	12,5 m/s <sup>2</sup>
Length of Stroke	28 mm
Product Dimensions (L x W x H):	499 x 91 x 234 mm
Strokes per Minute (SPM)	0 - 2900 min <sup>-1</sup>
Vibration Level (3 axes)	18,5 m/s <sup>2</sup>
Sound Power Level (L <sub>WA</sub> )	95 dB(A)
Voltage LXT	1
System	LXT 18V/36V
Product net weight (new)	3,1 kg
Vibration Uncertainty (K Factor)	2,0 m/s <sup>2</sup>
Noise Uncertainty (K Factor)	3 dB(A)
Tool Category	Sawing
Max. Cutting Capacity in Steel Pipe	130 mm

#### Standard Equipment

- ⦿ 1pc DC18RC Fast Charger
- ⦿ 2pcs BL1850B (5.0Ah) 18V LXT Battery
- ⦿ Carry Case

#### More info

<https://makita.ae/product/reciprocating-saw-lxt-djr181rte/>