



Reciprocating Saw LXT DJR185Z



Product Description

18V LXT • 0 – 3 300 min⁻¹ • 13 mm

Compact reciprocating saw for light use, also accepts jigsaw bits

A straight-framed light and small reciprocating saw offers access to tight places. Two separate switches enable diverse working postures. Stroke length of 13 mm, stroke rate can be adjusted between 0 – 3 300 min⁻¹ from a switch. LED light. Tool only, battery and charger not included.

Product Features

- ◎ LED light illuminates the work site
- ◎ Battery protection system automatically shuts off power when the battery level is low
- ◎ Body model - delivered without battery and charger.

Barcode

88381652353

Product Specifications

Vibration Level (3 axes), Cutting Wood	7,0 m/s ²
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
Tool weight with battery (EPTA)	1,5 - 1,8 kg
Battery Voltage	18 V
Max. Cutting Capacity in Wood (90°)	50 mm
Sound Pressure Level	76 dB(A)
Vibration Level (3 axes), Cutting Chipboard	8,0 m/s ²
Length of Stroke	13 mm
Product Dimensions (L x W x H):	398 x 81 x 220 mm
Strokes per Minute (SPM)	0 - 3000 min ⁻¹
Vibration Level (3 axes)	8,0 m/s ²
Voltage LXT	1
System	LXT 18V/36V
Product net weight (new)	1,2 kg
Vibration Uncertainty (K Factor)	1,5 m/s ²
Noise Uncertainty (K Factor)	3 dB(A)
Tool Category	Sawing
Max. Cutting Capacity in Steel Pipe	50 mm

Standard Equipment

- ◎ Sold without Battery or Charger

More info

<https://makita.ae/product/reciprocating-saw-lxt-djr185z/>