

Reciprocating Saw LXT

DJR187RTE



Product Description

18V LXT • 0 - 3 000 min⁻¹ • 32 mm

Efficient brushless reciprocating saw

An efficient brushless reciprocating saw for spark-free cutting of metal and demolition work for professional use. Two speed settings, stroke length of 32 mm and stroke rate of 0 - 2 800 min⁻¹ with continuous control from the switch. Quick-release blade attachment. Includes 2 x 5,0 Ah batteries and a charger in a case.

Product Features

- ⦿ LED light illuminates the work site
- ⦿ Battery protection system automatically shuts off power when the battery level is low

Barcode

88381806190

Product Specifications

| | |
|---|-----------------------------------|
| Vibration Level (3 axes), Cutting Wood | 15,5 m/s ² |
| Battery Chemistry (Ni-Cd / Ni-MH / Li-ion) | Li-ion |
| Tool weight with battery (EPTA) | 3,4 - 3,8 kg |
| Brushless Motor | YES |
| Battery Voltage | 18 V |
| Max. Cutting Capacity in Wood (90°) | 255 mm |
| Sound Pressure Level | 84 dB(A) |
| Vibration Level (3 axes), Cutting Chipboard | 16,5 m/s ² |
| Length of Stroke | 32 mm |
| Product Dimensions (L x W x H): | 439 x 83 x 231 mm |
| Strokes per Minute (SPM) | 0 - 2300 / 3000 min ⁻¹ |
| Vibration Level (3 axes) | 16,5 m/s ² |
| Sound Power Level (L _{WA}) | 95 dB(A) |
| Voltage LXT | 1 |
| System | LXT 18V/36V |
| Product net weight (new) | 3,1 kg |
| Vibration Uncertainty (K Factor) | 1,5 m/s ² |
| Noise Uncertainty (K Factor) | 3 dB(A) |
| Tool Category | Sawing |
| Max. Cutting Capacity in Steel Pipe | 130 mm |

Standard Equipment

- ⦿ 1pc DC18RC Fast Charger
- ⦿ 2pcs BL1850B (5.0Ah) 18V LXT Battery

⦿ Carry Case

More info

<https://makita.ae/product/reciprocating-saw-lxt-djr187rte/>