



## Reciprocating Saw LXT DJR187RTE



### Product Description

18V LXT • 0 – 3 000 min<sup>-1</sup> • 32 mm

#### Efficient brushless reciprocating saw

An efficient brushless reciprocating saw for spark-free cutting of metal and demolition work for professional use. Two speed settings, stroke length of 32 mm and stroke rate of 0 – 2 800 min<sup>-1</sup> with continuous control from the switch. Quick-release blade attachment. Includes 2 x 5,0 Ah batteries and a charger in a case.

### Product Features

- ◎ LED light illuminates the work site
- ◎ Battery protection system automatically shuts off power when the battery level is low

### Barcode

88381806190

### Product Specifications

<b>Vibration Level (3 axes), Cutting Wood</b>	15,5 m/s <sup>2</sup>
<b>Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)</b>	Li-ion
<b>Tool weight with battery (EPTA)</b>	3,4 - 3,8 kg
<b>Brushless Motor</b>	YES
<b>Battery Voltage</b>	18 V
<b>Max. Cutting Capacity in Wood (90°)</b>	255 mm
<b>Sound Pressure Level</b>	84 dB(A)
<b>Vibration Level (3 axes), Cutting Chipboard</b>	16,5 m/s <sup>2</sup>
<b>Length of Stroke</b>	32 mm
<b>Product Dimensions (L x W x H):</b>	439 x 83 x 231 mm
<b>Strokes per Minute (SPM)</b>	0 - 2300 / 3000 min <sup>-1</sup>
<b>Vibration Level (3 axes)</b>	16,5 m/s <sup>2</sup>
<b>Sound Power Level (L<sub>WA</sub>)</b>	95 dB(A)
<b>Voltage LXT</b>	1
<b>System</b>	LXT 18V/36V
<b>Product net weight (new)</b>	3,1 kg
<b>Vibration Uncertainty (K Factor)</b>	1,5 m/s <sup>2</sup>
<b>Noise Uncertainty (K Factor)</b>	3 dB(A)
<b>Tool Category</b>	Sawing
<b>Max. Cutting Capacity in Steel Pipe</b>	130 mm

### Standard Equipment

- ◎ 1pc DC18RC Fast Charger
- ◎ 2pcs BL1850B (5.0Ah) 18V LXT Battery

◎ Carry Case

More info

<https://makita.ae/product/reciprocating-saw-lxt-djr187rte/>