

Reciprocating Saw LXT

DJR360Z



Product Description

36V (18Vx2) LXT • 0 - 3 000 min⁻¹ • 32 mm

Extremely efficient brushless reciprocating saw

An efficient brushless saw for spark-free cutting of metal and demolition work. Two 18V LXT batteries achieve a voltage of 18V+18V. Two speeds, stroke length of 32 mm and stroke rate of 0 - 2 800 min⁻¹ with continuous control from the switch. Quick-release blade attachment. Tool only, battery and charger not included.

Product Features

- LED light illuminates the work site
- Battery protection system automatically shuts off power when the battery level is low

Barcode

88381806237

Product Specifications

Vibration Level (3 axes), Cutting Wood	15,5 m/s ²
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
Tool weight with battery (EPTA)	4,0 - 4,7 kg
Brushless Motor	YES
Battery Voltage	2 x 18 V
Max. Cutting Capacity in Wood (90°)	255 mm
Sound Pressure Level	88 dB(A)
Vibration Level (3 axes), Cutting Chipboard	16,5 m/s ²
Length of Stroke	32 mm
Product Dimensions (L x W x H):	449 x 116 x 243 mm
Strokes per Minute (SPM)	0 - 2300 / 3000 min ⁻¹
Vibration Level (3 axes)	16,5 m/s ²
Sound Power Level (L _{WA})	96 dB(A)
Voltage LXT	1
System	LXT 18V/36V
Product net weight (new)	3,3 kg
Vibration Uncertainty (K Factor)	1,5 m/s ²
Noise Uncertainty (K Factor)	3 dB(A)
Tool Category	Sawing
Max. Cutting Capacity in Steel Pipe	130 mm

Standard Equipment

- Sold without Battery or Charger

More info

<https://makita.ae/product/reciprocating-saw-lxt-djr360z/>