



## Reciprocating Saw XGT

# JR001GM201



### Product Description

40V MAX XGT • 0 - 3 000 min<sup>-1</sup> • 32 mm

#### Efficient brushless reciprocating saw

An efficient brushless reciprocating saw for spark-free cutting of metal and demolition work for professional use. Two speed settings, stroke length of 32 mm and stroke rate of 0 - 3 000 min<sup>-1</sup> with continuous control from the switch. Quick-release blade attachment. Includes two 4,0 Ah batteries and a rapid charger in a case.

### Product Features

- ◎ Toolless blade change and shoe adjustment
- ◎ Compact and ergonomic design
- ◎ Brushless maintenance-free and long-life motor
- ◎ Wide hanging hook, eg for scaffolding
- ◎ XPT (Extreme Protection Technology) is engineered for improved dust and water resistance for operation in harsh job site conditions
- ◎ Battery protection system automatically shuts off power when the battery level is low

### Barcode

88381893213

### Product Specifications

|  |                                   |
|--|-----------------------------------|
| <b>Vibration Level (3 axes), Cutting Wood</b>      | 19,5 m/s <sup>2</sup>             |
| <b>Tool weight with battery (EPTA)</b>             | 4,2 - 4,8 kg                      |
| <b>Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)</b>  | Li-ion                            |
| <b>Battery Voltage</b>                             | 40 V                              |
| <b>Brushless Motor</b>                             | YES                               |
| <b>Max. Cutting Capacity in Wood (90°)</b>         | 255 mm                            |
| <b>Sound Pressure Level</b>                        | 85 dB(A)                          |
| <b>Vibration Level (3 axes), Cutting Chipboard</b> | 18 m/s <sup>2</sup>               |
| <b>Length of Stroke</b>                            | 32 mm                             |
| <b>Product Dimensions (L x W x H):</b>             | 472 x 88 x 239 mm                 |
| <b>Strokes per Minute (SPM)</b>                    | 0 - 2300 / 3000 min <sup>-1</sup> |
| <b>Vibration Uncertainty (K Factor)</b>            | 1,5 m/s <sup>2</sup>              |
| <b>System</b>                                      | XGT 40Vmax/80V max                |
| <b>Vibration Level (3 axes)</b>                    | 18,0 m/s <sup>2</sup>             |
| <b>Sound Power Level (L<sub>WA</sub>)</b>          | 96 dB(A)                          |
| <b>Product net weight (new)</b>                    | 3,5 kg                            |
| <b>Voltage XGT</b>                                 | 1                                 |
| <b>Noise Uncertainty (K Factor)</b>                | 3 dB(A)                           |
| <b>Max. Cutting Capacity in Steel Pipe</b>         | 130 mm                            |

## Standard Equipment

- ◎ 1pc DC40RA Fast Charger
- ◎ 2pcs x BL4040 (4.0Ah) 40V MAX XGT Battery
- ◎ Plastic Case

## More info

<https://makita.ae/product/reciprocating-saw-xgt-jr001gm201/>